SIEMENS

Data sheet 6ES7151-1CA00-1BL0

	*** spare part *** ET 200S Compact, 32DI STD, 24 V DC, 3 ms, expandable by up to 12 modules of the ET 200S (no F modules) electronics block
General information	
Product function	
● Isochronous mode	No
Supply voltage	
Load voltage 1L+	
● Rated value (DC)	24 V
● Reverse polarity protection	Yes
Input current	
from supply voltage 1L+, max.	100 mA
Power loss	
Power loss, typ.	3 W
Address area	
Address space per module	
● Inputs	100 byte
● Outputs	100 byte
Digital inputs	
Number of digital inputs	32
Input voltage	
● Type of input voltage	DC
● Rated value (DC)	24 V
● for signal "0"	-30 to +5 V
● for signal "1"	13 to 30V
Input current	
● for signal "1", typ.	4 mA; At 24 V min. 2 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", min.	1.2 ms; typically 3 ms
— at "0" to "1", max.	4.8 ms; typically 3 ms
— at "1" to "0", min.	1.2 ms; typically 3 ms
— at "1" to "0", max.	4.8 ms; typically 3 ms
Cable length	
● unshielded, max.	1 000 m
Digital outputs	
Type of digital output	without
Number of digital outputs	0
1. Interface	
Interface types	
● RS 485	Yes
Interface types	
RS 485	
● Cable length, max.	1 200 m
Protocols	
PROFIBUS DP	Yes
PROFIBUS DP	
Services	
— Direct data exchange (slave-to-slave communication)	Yes
Interrupts/diagnostics/status information	
Alarms	No

Subject to change without notice
© Copyright Siemens

Diagnostics function	Yes
Diagnostics indication LED	
● Bus fault BF (red)	Yes
● Group error SF (red)	Yes
● Monitoring 24 V voltage supply ON (green)	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	120 mm
Height	81 mm
Depth	58 mm
Classifications	

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration | Miscellaneous | UL | RCM | EAC | China RoHS

EMV | **For use in hazardous locations**

RCM | ATEX | FM | ATEX | UL | IECEx

For use in hazardous locations | **Maritime application**

CCC-Ex | ABS | BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai

Maritime application

RINA | CCS (China Classification Society) | KR (Korean Register of Shipping)

Subject to change without notice
© Copyright Siemens

last modified: 9/11/2026

Subject to change without notice
© Copyright Siemens