SIEMENS

Data sheet for SIMOTICS S-1FK7

Article No. : **1FK7043-7AH71-1FH0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed (100 K)	4,500 rpm
Number of poles	6
Rated torque (100 K)	2.6 Nm
Rated current	4.0 A
Static torque (60 K)	2.50 Nm
Static torque (100 K)	3.10 Nm
Stall current (60 K)	3.60 A
Stall current (100 K)	4.50 A
Moment of inertia	1.140 kgcm²
Efficiency	90.0 %

Physical constants	
Torque constant	0.67 Nm/A
Voltage constant at 20° C	44.0 V/1000*min⁻¹
Winding resistance at 20° C	1.20 Ω
Rotating field inductance	15.0 mH
Electrical time constant	12.50 ms
Mechanical time constant	0.81 ms
Thermal time constant	40 min
Shaft torsional stiffness	11,000 Nm/rad
Net weight of the motor	7.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.08 mm
Axial runout tolerance	0.08 mm
Vibration severity grade	Grade A
Connector size	M23
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	with holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

Optimum operating point	
Optimum speed	4,500 rpm
Optimum power	1.2 kW

Limiting data	
Max. permissible speed (mech.)	8,000 rpm
Max. permissible speed (inverter)	13,100 rpm
Maximum torque	9.4 Nm
Maximum current	14.8 A

Holding brake	
Holding brake version	Permanent-magnet brake
Holding torque	4.0 Nm
Power supply voltage	DC 24 V ± 10 %
Coil current	0.5 A
Opening time	70 ms
Closing time	30 ms
Highest braking work	150 J

Recommended Motor Module	
Rated inverter current	5 A
Maximum inverter current	10 A
Maximum torque	6.80 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens