SIEMENS

Data sheet 3SU1400-1GE10-1AA0

Siemens EcoTech

electronic module IO-Link for RFID key-operated switch, freely programmable electronic switch, controller and RFID authentication of the switching function, black, operating voltage 24 V DC, screw terminal, for front plate mounting, for industrial application in control cabinets and machines



product brand name	SIRIUS ACT
product designation	Electronic module for ID key-operated switches
product type designation	3SU1
Actuator	
product extension optional light source	No
Contact block/ lampholder	
socket design	other
Display	
number of LEDs	4
General technical data	
insulation voltage rated value	30 V
degree of pollution	3
type of voltage	
● of the operating voltage	DC
● of the input voltage	DC
surge voltage resistance rated value	0.8 kV
consumed current maximum	49 mA
protection class IP	IP20, clamping screw tightened
reference code according to IEC 81346-2	P
Substance Prohibitance (day/month/year)	10/01/2014
SVHC substance name	Lead CAS-No. 7439-92-1 Lead monoxide (lead oxide) CAS-No. 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1
Net Weight	45.38 g
operating voltage	
● rated value	18 ... 30 V
● **at DC rated value**	24 V
operating voltage 1 at DC rated value	24 V
Communication/ Protocol	
protocol is supported IO-Link protocol	Yes
IO-Link transfer rate	COM2 (38,4 kBaud)
point-to-point cycle time between master and IO-Link device minimum	10 ms
type of voltage supply via input/output link master	Yes
data volume	

Subject to change without notice
© Copyright Siemens

● of the address range of the inputs with cyclical transfer total	2 byte
● of the address range of the outputs with cyclical transfer total	0 byte
Auxiliary circuit	
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	5
Inputs/ Outputs	
number of digital inputs	0
● safety-related	0
number of digital outputs	5
output voltage at digital output at DC rated value	23.5 V
output current per output	250 mA
Connections/ Terminals	
type of electrical connection	screw terminal
type of connectable conductor cross-sections	
● solid without core end processing	1x (0.2 ... 2.5 mm²)
● finely stranded with core end processing	1x (0.25 ... 1.5 mm²), 2x (0.5 ... 0.75 mm²)
● finely stranded without core end processing	1x (0.2 ... 2.5 mm²), 2x (0.2 ... 0.75 mm²)
● for AWG cables	1x (26 ... 14)
tightening torque with screw-type terminals	0.4 N·m
Product Function	
product function parameterizable	Yes
Safety related data	
MTBF	
● at 70 °C	138 a
● at full load at 25 °C	141 a
Electrical Safety	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
● during operation	-25 ... +70 °C
● during storage	-40 ... +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95%, no condensation in operation permitted)
Installation/ mounting/ dimensions	
fastening method	front plate mounting
● of modules and accessories	Front plate mounting
height	36 mm
width	50 mm
depth	36.4 mm
required spacing with side-by-side mounting	
● forwards	100 mm
● backwards	100 mm
● upwards	100 mm
● downwards	100 mm
● at the side	100 mm
Measuring circuit	
product function	IO-Link 24 V DC
Environmental footprint	
Environmental Product Declaration(EPD)	Yes
global warming potential [CO2 eq] total	0.787 kg
global warming potential [CO2 eq] during manufacturing	0.566 kg
global warming potential [CO2 eq] during operation	0.235 kg
global warming potential [CO2 eq] after end of life	-0.015 kg
Approvals Certificates	
Environmental Product Declaration	
● global warming potential [CO2 eq] / during manufacturing	0.566 kg
● global warming potential [CO2 eq] / during operation	0.235 kg

Subject to change without notice
© Copyright Siemens

• global warming potential [CO2 eq] / after end of life	-0.0145 kg
• global warming potential [CO2 eq] / total	0.787 kg


Environment	General Product Approval

Environmental Confirmations


Test Certificates		other	
Type Test Certificates/Test Report	Special Test Certificate	Confirmation	产品合格 QC PASS

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-1GE10-1AA0
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-1GE10-1AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1GE10-1AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-1GE10-1AA0&lang=en



© Copyright Siemens



last modified: 7/4/2026

Subject to change without notice
© Copyright Siemens