SIEMENS

## Data sheet 6ES7131-6CF00-0AU0







SIMATIC ET 200SP, digital input module, DI 8x 24 V AC..48 V UC Basic, packing quantity: 1 unit, suitable for BU type U0, color code CC20, module diagnostics

| | |
|---|---|
| **General information** | |
| Product type designation | DI 8x24VAC/48VUC BA |
| HW functional status | From FS02 |
| Firmware version | V0.0 |
| ● FW update possible | No |
| usable BaseUnits | BU type U0 |
| Product function | |
| ● I&M data | Yes; I&M0 to I&M3 |
| ● Isochronous mode | No |
| ● suitable for operation on PROFINET R1 IMs | Yes |
| Engineering with | |
| ● STEP 7 TIA Portal configurable/integrated from version | V15 |
| ● STEP 7 configurable/integrated from version | V5.6 |
| ● PROFIBUS from GSD version/GSD revision | One GSD file each, Revision 3 and 5 and higher |
| ● PROFINET from GSD version/GSD revision | GSDML V2.3 |
| Operating mode | |
| ● DI | Yes |
| ● Counter | No |
| ● Oversampling | No |
| ● MSI | No |
| **Supply voltage** | |
| Rated value (DC) | 48 V |
| permissible range, lower limit (DC) | 40.8 V |
| permissible range, upper limit (DC) | 57.6 V |
| Rated value (AC) | 48 V; 24 V/48 V; 50 Hz/60 Hz |
| permissible range, lower limit (AC) | 40.8 V |
| permissible range, upper limit (AC) | 52.8 V |
| Reverse polarity protection | Yes |
| **Input current** | |
| Current consumption, max. | 70 mA; without sensor supply |
| **Encoder supply** | |
| Number of outputs | 8 |
| Short-circuit protection | Yes; Per module, 5x 20 mm fuse, 2 A/250 V, quick-response, replaceable |
| Output current | |
| ● up to 60 °C, max. | 1 A |
| 24 V encoder supply | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● 24 V | No |
| **Power loss** | |
| Power loss, typ. | 1.5 W |
| **Address area** | |
| Address space per module | |
| ● Address space per module, max. | 1 byte |
| **Hardware configuration** | |
| Automatic encoding | |
| ● Mechanical coding element | Yes |
| ● Type of mechanical coding element | type C |
| Selection of BaseUnit for connection variants | |
| ● 1-wire connection | BU type U0 |
| ● 2-wire connection | BU type U0 |
| ● 3-wire connection | BU type U0 + Potential distributor module |
| ● 4-wire connection | BU type U0 + Potential distributor module |
| **Digital inputs** | |
| Number of digital inputs | 8 |
| Sourcing/sinking input | P-reading |
| Input characteristic curve in accordance with IEC 61131, type 1 | Yes |
| Input characteristic curve in accordance with IEC 61131, type 2 | No |
| Input characteristic curve in accordance with IEC 61131, type 3 | No |
| Pulse extension | No |
| Input voltage | |
| ● for signal "0" | AC/DC < 10 V |
| ● for signal "1" | AC > 14 V, DC > 34 V |
| Input current | |
| ● for signal "1", typ. | 3.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | No |
| — at "0" to "1", max. | 15 ms |
| — at "1" to "0", max. | 20 ms |
| Cable length | |
| ● shielded, max. | 1 000 m |
| ● unshielded, max. | 600 m |
| **Encoder** | |
| Connectable encoders | |
| ● 2-wire sensor | Yes |
| **Interrupts/diagnostics/status information** | |
| Diagnostics function | Yes |
| Alarms | |
| ● Diagnostic alarm | Yes |
| Diagnoses | |
| ● Diagnostic information readable | Yes |
| ● Monitoring the supply voltage | Yes |
| ● Monitoring of encoder power supply | Yes |
| ● Group error | Yes |
| Diagnostics indication LED | |
| ● Monitoring of the supply voltage (PWR-LED) | Yes; green PWR LED |
| ● Channel status display | Yes; green LED |
| ● for channel diagnostics | No |
| ● for module diagnostics | Yes; green/red DIAG LED |
| **Potential separation** | |
| Potential separation channels | |
| ● between the channels | No |
| ● between the channels and backplane bus | Yes |
| ● between the channels and the power supply of the electronics | No |
| **Isolation** | |


© Copyright Siemens

| | |
|---|---|
| Isolation tested with | 1 200 V DC between supply voltage and backplane bus |
| **Standards, approvals, certificates** | |
| Suitable for safety functions | No |
| Ecological footprint | |
| ● environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 15.9 kg |
| — global warming potential, (during production) [CO2 eq] | 3.69 kg |
| — global warming potential, (during operation) [CO2 eq] | 12.7 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.495 kg |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● horizontal installation, min. | -30 °C |
| ● horizontal installation, max. | 60 °C |
| ● vertical installation, min. | -30 °C |
| ● vertical installation, max. | 50 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 2 000 m; On request: Installation altitudes greater than 2 000 m |
| Absolute humidity | |
| ● dew point, min. | -60 °C; suitable for dry room applications |
| **Dimensions** | |
| Width | 20 mm |
| Height | 73 mm |
| Depth | 58 mm |
| **Weights** | |
| Weight, approx. | 40 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-26-04 |
| eClass | 14 | 27-24-26-04 |
| eClass | 12 | 27-24-26-04 |
| eClass | 9.1 | 27-24-26-04 |
| eClass | 9 | 27-24-26-04 |
| eClass | 8 | 27-24-26-04 |
| eClass | 7.1 | 27-24-26-04 |
| eClass | 6 | 27-24-26-04 |
| ETIM | 10 | EC001599 |
| ETIM | 9 | EC001599 |
| ETIM | 8 | EC001599 |
| ETIM | 7 | EC001599 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

**Approvals / Certificates**

**General Product Approval**

Manufacturer Declaration | Miscellaneous

| General Product Approval | For use in hazardous locations |
|---|---|


Subject to change without notice
© Copyright Siemens

China RoHS

| For use in hazardous locations | Maritime application | | | | |
|---|---|---|---|---|---|
| FM | ABS | BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai |

| Maritime application | | | Environment | |
|---|---|---|---|---|
| RINA | CCS (China Classification Society) | KR (Korean Register of Shipping) | EPD | Siemens EcoTech |

**last modified:** 2/1/2026


Subject to change without notice
© Copyright Siemens