SIEMENS

Data sheet 3VL3720-1SP36-0AB1

circuit breaker VL250N standard breaking capacity Icu=55kA, 415V AC 3-pole, motor/generator prot. Electronic Trip Unit ETU10M, LI In=200A, rated current IR=80...200A, overload protection, II=1.25 to 11xIN, short-circuit protection without auxiliary release Auxiliary switch mounting kit 2 AUX (1 NO + 1 NC)

Weight	2.5 kg
Net Weight	2.5 kg

Approvals / Certificates

Environment		General Product Approval			
Environmental Confirmations	Environmental Confirmations			Confirmation	

Test Certificates	other			Dangerous goods	
Special Test Certificate	Miscellaneous	Confirmation		Miscellaneous	Transport Information

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3720-1SP36-0AB1
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL3720-1SP36-0AB1
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3720-1SP36-0AB1
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL3720-1SP36-0AB1

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens