SIEMENS

Error:
No CAD-Data available for this configuration.

Data sheet for SINUMERIK Machine Push Button Panel MPP 483 IEH

Article No. : 6FC5303-1AF10-8AA0

Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Input voltage	DC 24 V
Power consumption, max.	35.0 W

Mechanical data	
Net weight	3.000 kg (6.61 lb)
Dimensions	
Width	483.0 mm (19.02 in)
Height	155.0 mm (6.10 in)
Depth	200.0 mm (7.87 in) With connector for handwheel connection
Installation depth	140.0 mm (5.51 in) Without connector for handwheel Connection 105 mm (4.13 in)
Mounting surface	
Cutout width	451.0 mm (17.76 in)
Cutout height	137.6 mm (5.42 in)
Degree of protection	
Rear side	IP10A
Front side	IP54

Ambient conditions	
Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Ambient temperature	
Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Relative humidity	
Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CE, UL