SIEMENS

Data sheet for SIMOTICS S-1FT7




Figure similar

Article No. : 1FT7136-5AB71-1BA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data	
Rated speed	1,500 rpm
Number of poles	8
Rated torque (100 K)	92.0 Nm
Rated current	25.00 A
Static torque (60 K)	115.0 Nm
Static torque (100 K)	140.0 Nm
Stall current (60 K)	29.50 A
Stall current (100 K)	36.00 A
Rotor moment of inertia	748.00 kgcm²
Efficiency	94.0 %

Physical constants	
Torque constant	3.88 Nm/A
Voltage constant at 20° C	255.0 V/1000*min^{-1}
Winding resistance at 20° C	0.10 Ω
Rotary field inductance	3.9 mH
Electrical time constant	38.00 ms
Mechanical time constant	1.50 ms
Thermal time constant	90 min
Shaft torsional stiffness	301,000 Nm/rad
Net weight of the motor	108.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	132
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.125 mm
Axial runout tolerance	0.125 mm
Vibration severity grade	Grade A
Degree of protection	IP65
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Fitted key and keyway
Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Safety Integrated - Suitable encoder	Yes
Electrical connection	Connector turnable
Connector size	1.5

Optimum operating point	
Optimum speed	1,500 rpm
Optimum power	14.5 kW

Limiting data	
Max. permissible speed (mech.)	3,600 rpm
Max. permissible speed (inverter)	2,250 rpm
Maximum torque	490.0 Nm
Maximum current	154.00 A

Recommended Motor Module	
Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	305.0 Nm

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens