SIEMENS

Data sheet 3KL7142-4AD00

SECTION FUS-NH 4x 400 A COMM MOT

Model	
product designation	switch disconnector with fuses
Protection class	
protection class IP	IP00
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	20.8 W
Main circuit	
operational current rated value	400 A
Mechanical Design	
Net Weight	1 kg
Approvals Certificates	

Environment		General Product Approval	other	
Environmental Confirmations	Environmental Confirmations	EAC	Confirmation	Confirmation	产品合格 QC PASS

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…) https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7142-4AD00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3KL7142-4AD00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7142-4AD00
CAx-Online-Generator https://www.siemens.com/cax
Tender specifications https://www.siemens.com/specifications
Kennlinien https://curves.simaris.siemens.com/curves/3KL7142-4AD00

last modified: 5/16/2026

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens