SIEMENS

Data sheet 3NP5260-0CA10



SENTRON, Fuse switch disconnector 3NP5, 3-pole, NH1, 250 A, for assembly and installation on mounting plate, with High-speed closing, screw terminal, Auxiliary switch on switch disconnector: 1 NO+1 NC

Model	
product brand name	SENTRON
product designation	3NP5 fuse switch disconnector
design of the product	auxiliary switch at the switch disconnector: 1 NO + 1 NC
design of the actuating element	Cover handle
design of the load switch strip form	No
General technical data	
number of poles	3
size of disconnecting link	NH0, NH1
size of fuse link	NH0, NH1
mounting type	Fixed mounting
fuse system	LV HRC fuse
Voltage	
insulation voltage rated value	690 V
surge voltage resistance rated value	6 kV
operating voltage	
● at AC rated value maximum	690 V
● at DC rated value	440 V
Protection class	
protection class IP on the front	IP00
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	2.66 W
Main circuit	
operational current rated value	250 A
Suitability	
suitability for use main switch	No
suitability for use switch disconnector	Yes
suitability for use EMERGENCY OFF switch	No
Product function	
product function fuse monitoring	No
Short circuit	
maximum short-circuit current breaking capacity (Icu) at 400 V rated value	2.5 kA
Connections	
type of electrical connection	6 - 150 mm²
● for main current circuit	screw-type terminals
Mechanical Design	
height	300 mm

Subject to change without notice
© Copyright Siemens

width	207 mm
depth	176 mm
fastening method	Mounting plate
fastening method	
● floor mounting	Yes
● rail mounting	No
Net Weight	5.248 kg

Environmental conditions

installation altitude at height above sea level maximum	2 000 m
ambient temperature during operation	
● minimum	-25 °C
● maximum	55 °C
ambient temperature during storage	
● minimum	-50 °C
● maximum	80 °C

Approvals Certificates


Environment		General Product Approval				
Environmental Confirmations	Environmental Confirmations			Miscellaneous		

General Product Approval	Test Certificates	other	
	Type Test Certificates/Test Report	Confirmation	

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NP5260-0CA10
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3NP5260-0CA10
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP5260-0CA10
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/3NP5260-0CA10

Subject to change without notice
© Copyright Siemens



last modified: 4/11/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens