SIEMENS

Data sheet 6AV6881-0AD56-0AA0



pipe adapter VESA 100/75, IP20, for Pro devices, scope of supply: 1 pipe adapter

General information	
Product type designation	VESA 100/75 flange adapter
Installation type/mounting	
Mounting	VESA 100 mm / 75 mm with M6 thread
Mounting type	Support arm with VESA 100 mm or 75 mm
Degree and class of protection	
IP (at the front)	IP20 (depending on mounting)
Standards, approvals, certificates	
responsibility with the manufacturer	Yes
CE mark	No; No CE marking obligation
REACH	Yes; Tested
RoHS conformity	Yes; Tested / compliant
Use in hazardous areas	
● ATEX Zone 2	No
● ATEX Zone 22	No
● ATEX as target device	No
● IECEx Zone 1	No
● IECEx Zone 11	No
● IECEx Zone 2	No
● IECEx Zone 22	No
● cULus Class I Zone 1	No
● cULus Class I Zone 2, Division 2	No
● cULus Class II Division 2	No
● FM Class I Division 2	No
● FM Class II Division 2	No
Marine approval	
● Germanischer Lloyd (GL)	No
● American Bureau of Shipping (ABS)	No
● Bureau Veritas (BV)	No
● Det Norske Veritas (DNV)	No
● Korean Register of Shipping (KRS)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (Class NK)	No
● Polski Rejestr Statkow (PRS)	No
● Chinese Classification Society (CCS)	No
● Marine approval as target device	No
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No

Subject to change without notice
© Copyright Siemens

Ambient temperature during operation	
● min.	0 °C
● max.	55 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	70 °C
Relative humidity	
● Operation, max.	60 %
● Condensation permissible	No; No
Mechanics/material	
Material	steel
● Sheet metal	Yes
Dimensions	
Width	135 mm
Height	120 mm
Depth	67.5 mm
Weights	
Weight (without packaging)	1.48 kg
Scope of supply	
Delivery quantity in pieces	1; VESA round tube adapter 100/75 suitable for PRO devices, max. IP20 attainable
Other	
Merchandise	Yes
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
contacting the manufacturer	email: querumproducts@web.de
Target devices	Not suitable for 19" 4:3 devices
Note:	Max. load 35 kg, for expandable support arm mounting

Classifications

	Version	Classification
eClass	16	27-33-02-92
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval	**other**

Manufacturer Declaration | Miscellaneous

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW

Subject to change without notice
© Copyright Siemens

last modified: 9/25/2026

Subject to change without notice
© Copyright Siemens