SIEMENS

Data sheet 6GK6000-8FX04-4EA0

product type designation	**RUGGEDCOM 2488-24FXA04 Module**
	Media Module for RUGGEDCOM RSG2488, 4 x 100MBit/s ST-interface, Optical: 100BASE-FX, Single Mode fiber optic up to 20 kilometer, 1310nm



Figure similar

product brand name	RUGGEDCOM
Technical Product Detail Page	https://i.siemens.com/1P6GK6000-8FX04-4EA0
suitability for operation	RSG2488
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of optical interfaces / for network components or terminal equipment / maximum	4
number of 100 Mbit/s ST(BFOC) ports / for multimode / integrated	4
design of the optical interface / for network components or terminal equipment	ST
range / at the optical interface / depending on the optical fiber used	20 km
ambient conditions	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• note	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40 (when installed)
design, dimensions and weights	
design	Media module
width	110 mm
height	22 mm
depth	91 mm
net weight	0.43 kg
product feature / conformal coating	No
fastening method	screwed
• installation in media module slot	Yes
standards, specifications, approvals	
standard	
• for EMC	FCC Part 15 (Class A), EN55022 (CISPR22 Class A)
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
• for hazardous zone / from CSA and UL	Hazardous Locations: Class 1 Division 2
• for emitted interference	EN 61000-6-4 (Class A)

Subject to change without notice
© Copyright Siemens

● for interference immunity	EN 61000-6-2
laser protection class	21 CFR Chapter 1, Subchapter J
certificate of suitability	EN 61000-6-2, EN 61000-6-10
● CE marking	Yes
● C-Tick	No
● KC approval	No
● E1 approval	No
● IEC 61850-3	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	259.55 kg
● during manufacturing	13.3 kg
● during operation	246.21 kg
● after end of life	0.04 kg
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to website: Industry Mall/RUGGEDCOM selector	https://www.siemens.com/ruggedcom-selector
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to website: Siemens RUGGEDCOM	https://www.siemens.com/ruggedcom
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval	other	Environment
Manufacturer Declaration	inspection certificate	EPD

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens