SIEMENS

Data sheet 6ES7132-7GD10-0AB0



SIMATIC, electronic module for ET200iSP, 4 DO, 17.4 V DC/27 mA, "L"-shutdown, Ex ib (ia Ga) IIC T4 Gb, Ex ib [ia IIIC Da] IIC T4 Gb, Ex ib [ia] I Mb

General information	
Product type designation	4DQ 17.4 V DC/27 mA
HW functional status	7
Firmware version	V3.0.0
Installation type/mounting	
Rack mounting	No
Front mounting	Yes
Rail mounting	Yes
Wall mounting/direct mounting	No
Supply voltage	
Type of supply voltage	DC
Input current	
Current consumption, typ.	260 mA
from load voltage (power bus), max.	300 mA; with actuator supply
Power loss	
Power loss, typ.	2.1 W
Address area	
Address space per module	
● Address space per module, max.	2 byte
Hardware configuration	
Fieldbus connection via separate transceiver	Yes
Digital outputs	
Type of digital output	Transistor
Number of digital outputs	4; additionally 1 intrinsically-safe input for L shutdown
Short-circuit protection	Yes
No-load voltage Uao (DC)	17.4 V
Internal resistor Ri	150 Ω
Trend key points E	
● Voltage Ue (DC)	13.3 V
● Current Ie	27 mA; 54 mA when outputs connected in parallel
Output voltage	
● Type of output voltage	DC
Output current	
● for signal "1" rated value	0.027 A
Output delay with resistive load	
● "0" to "1", max.	2 ms
● "1" to "0", max.	1.5 ms
Parallel switching of two outputs	
● for uprating	Yes

Subject to change without notice
© Copyright Siemens

Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load, max.	2 Hz
Cable length	
● shielded, max.	500 m
● unshielded, max.	500 m
Interfaces	
Number of PROFINET interfaces	0
Number of RS 485 interfaces	0
Protocols	
Supports protocol for PROFINET IO	No
PROFIsafe	No
PROFIBUS	No
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes; Parameterizable
● Hardware interrupt	No
Diagnoses	
● Diagnostic information readable	Yes
● Wire break	Yes; R > 10 kohms, I < 100 µA
● short-circuit	Yes; R< 80 Ohm (one output), R< 40 Ohm (outputs connected in parallel)
Diagnostics indication LED	
● Group error SF (red)	Yes
● Status indicator digital output (green)	Yes
Ex(i) characteristics	
Module for Ex(i) protection	Yes; for more Co/Lo combinations, see certificate IECEx KEM 05.0011
maximum values for connecting terminals for gas group IIC	
● Uo (no-load voltage), max.	19.4 V
● Io (short-circuit current), max.	132 mA
● Po (power output), max.	0.64 W
● Co (permissible external capacity), max.	0.23 µF
● Lo (permissible external inductivity), max.	1.9 mH
● Ui (intrinsically safe input voltage), max.	28 V; switch input circuit
● Pi (intrinsically safe input power), max.	1.2 W; switch input circuit
● Ci (internal capacity), max.	3 nF; switch input circuit
Potential separation	
Potential separation digital outputs	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Degree and class of protection	
IP degree of protection	IP30
Standards, approvals, certificates	
CE mark	CE 0344
UKCA mark	DEKRA 21UKEX0085 Importer UK: Siemens plc Manchester M20 2UR
cULus	LISTED E334384
FM approval	CLASSIFIED 3025852
Suitable for safety functions	No
INMETRO certificate	UL-BR 12.0073
reference designation according to IEC 81346-2 (2009)	K
Highest safety class achievable in safety mode	
● SIL acc. to IEC 61508	No
Use in hazardous areas	
● ATEX marking	II 2 G (1) G Ex ib [ia Ga] IIC T4 Gb II 2 G (1) D Ex ib [ia IIIC Da] IIC T4 Gb I M2 Ex ib [ia] I Mb
● ATEX certificate	KEMA 04 ATEX 1249
● IECEx	IECEx KEM 05.0011
● CCC Ex	2020322316002945

© Copyright Siemens

● EAC Ex	PB Ex ib [ia] I Mb 1Ex ib [ia Ga] IIC T4 Gb [Ex ia Da] IIIC
● FM marking	Class I, Zone 1 AEx ib [ia] IIC T4 Ex ib IIC T4 NI, Class I, DIV.2, GP. A,B,C,D T4 AIS, Class I, DIV.1, GP. A,B,C,D T4 DIP Class II, III, GP. E,F,G
● Explosion protection category for gas	ATEX gas explosion protection, Zone 1
● Explosion protection category for dust	ATEX dust explosion protection, Zone 21 always install in corresponding enclosure
● associated equipment (Ex ia)	Yes
● associated equipment (Ex ib)	Yes
Marine approval	
● Germanischer Lloyd (GL)	Yes
● American Bureau of Shipping (ABS)	Yes
● Bureau Veritas (BV)	Yes
● Det Norske Veritas (DNV)	Yes
Connection method	
Design of electrical connection	Screw/spring-type terminal
Dimensions	
Width	30 mm
Height	129 mm
Depth	136.5 mm
Weights	
Weight, approx.	255 g

Classifications

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | China RoHS

General Product Approval	For use in hazardous locations				
Manufacturer Declaration	ATEX	IECEx	FM	IECEx	Miscellaneous

For use in hazardous locations

Subject to change without notice
© Copyright Siemens

	CCC-Ex			Miscellaneous	Miscellaneous

Maritime application

				NK / Nippon Kaiji Kyokai	

Environment



last modified: 7/7/2025

Subject to change without notice
© Copyright Siemens