SIEMENS

Data sheet for SIMOTICS S-1FT2

Article No. : **1FT2208-3SF01-2MB0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :


Basic motor data	
Motor type	Permanent-magnet synchronous motor, Forced ventilation, IP65
Motor type	Compact
Static torque	22.00 Nm
Static current	14.1 A
Maximum torque	51.00 Nm
Maximum current	40.0 A
Maximum speed	6,000 rpm
Rotor moment of inertia	29.6000 kgcm²
Weight	14.9 kg

Rated data	
SINAMICS S120, BLM/SLM 3AC 400V	
Rated speed	3,000 rpm
Rated torque	17.60 Nm
Rated current	12.2 A
Rated power	5.50 kW

Encoder system	
Encoder system	Encoder AM22DQC: Absolute encoder 22 bit + 12 bit multiturn
Safety Integrated - Suitable encoder	Yes

Motor connection	
Connection type	Double cable connection for S120
Connector size power connector	M23
Connector size signal connector	M17

Mechanical data	
Design acc. to Code I	IM B5 (IM V1, IM V3)
Vibration severity grade	Grade A
Shaft height	80
Flange size (AB)	155 mm
Centering ring (N)	130 mm
Hole circle (M)	165 mm
Screw-on hole (S)	11.0 mm
Overall length (LB)	283 mm
Diameter of shaft (D)	24 mm
Length of shaft (E)	50 mm
Length of flange diagonal (P)	194 mm
Shaft end	Plain shaft
Color of the housing	Standard (Anthracite, similar to RAL 7016)



Fan unit	
Operating voltage	24 V
Current	1.1 A
Plug	Standard M12, 5-pole, code A