SIEMENS

# Data sheet for Line reactor



Figure similar

**Article No. :** **6SE6400-3CC00-4AB3**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

## Rated data

| | |
|---|---|
| **Input** | |
| Number of phases | 1 AC |
| Line voltage | 200 ... 240 V |
| **Output** | |
| Rated current | 3.4 A |

## Mechanical data

| | |
|---|---|
| **Dimensions** | |
| Width | 75.5 mm (3.0 in) |
| Height | 200.0 mm (7.9 in) |
| Depth | 50.0 mm (2.0 in) |
| Degree of protection | IP20 / UL open type |
| Net weight | 1.3 kg (2.9 lb) |

## Connections

| | |
|---|---|
| **Line side** | |
| Version | screw-type terminal |
| Conductor cross-section | 1.00 ... 2.50 mm² (18 ... 14 AWG) |
| **Load side** | |
| Version | Pigtail |
| Conductor cross-section | 1.50 mm² |
| Cable length | 0.39 m (1.28 ft) |
| **PE connection** | |
| Version | M5 stud |

## Standards

| | |
|---|---|
| Compliance with standards | cURus |

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens