

Data sheet:

Web-IO 4.0 Digital, 12xIn, 8xRelay Out



Article no.: 57738

448.00 €

*Net price for commercial users

Switch, monitor and count ...

With the Web-IO 4.0 Digital [switching signals](#) can be controlled, acquired and monitored over TCP/IP Ethernet. Numerous web and network services are available for reporting changes on the inputs and outputs - even directly in a browser. With protocols such as [OPC UA](#), [MQTT](#) and [REST](#) the Web-IO is an ideal fit in the world of Industry 4.0 and the Internet of Things.

Properties

Switching signals:

- **12 switching inputs:**
 - Digital 24V inputs
 - 32-bit pulse counter
- **7 potential-free contacts as changeover**
- **1 potential-free contact as normally open**
 - Switching voltage up to 24V (110V, 230V via [coupling relays](#))
 - Switching current max. 2A

Wiring example

Connectivity:

- **Intuitive Web interface** for simpler operation
 - Select between German or English
 - [Switching the outputs directly from the Web interface](#)
 - [Adaptation for smartphone](#)
 - HTTP and HTTPS
- **Current Industry 4.0 protocols:**
 - [OPC UA](#), REST and [MQTT](#) support
 - AMQP on request
- **Box-to-Box**
 - [Pass switching signals over the network 1:1](#)
- **Alarm and reporting functions:**
 - [Email for alarm sending or as status report](#)
 - [SNMP polling / alarm traps V1 V2 V3](#)
 - Switching your outputs in alarm situations
 - Switching the outputs on another Web-IO
 - HTTP requests for controlling third-party devices
 - Up to 30 actions can be configured
- **Dynamic integration into other Web sites:**
 - Direct access to current IO states via [HTTP requests](#), [AJAX](#) and [JavaScript](#)
- **Additional software interfaces for incorporating into your systems/databases:**
 - [OPC UA](#), [OPC DA](#)
 - [Modbus TCP](#)
 - Syslog, SNMP V1 V2 V3

- [TCP and UDP sockets, client and server](#)
- [HTTP, HTTPS, AJAX](#)
- [FTP \(data logging\)](#)
- **Internal clock**
 - Time synchronization using time server calibration
 - Battery-backed device clock
- **Possible applications:**
 - Remote monitoring and fault messaging
 - Cross-location switching
 - House and building automation
 - Process monitoring and visualization
 - Light, gate and cabinet control
 - Machine Data Collection (MDC)
 - More uses can be found [here](#).

Power supply:

- **External power**
 - Screw terminal
 - 12 - 24V DC
- **PoE - Power over Ethernet**
 - Phantom power using data pairs
 - Power over unused wire pairs

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance per EN 61000-6-2
 - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3
- **5 year guarantee**

Wish for something!

[Your suggestions for improvement and additions](#)

Technical data

Connections, displays and control elements:

Digital outputs:	8 x potential-free contact max. 24V DC, 2A / 24V AC, 2A Using our coupling relays voltages of even up to 230V can be switched
Digital inputs:	12 x digital inputs, max. input voltage +/-30V protected against reverse connection within this range Switching threshold 4V +/- 0.5V "On" current = 2.2 mA integrated 32-bit pulse counter
Network:	10/100BaseT autosensing
Power supply:	12-24V DC (approx. 100mA@24V) PoE - Power over Ethernet
Galvanic isolation:	Digital outputs - network: min. 1000 V Digital inputs - network: min. 2000 V Digital inputs - outputs: min. 1000 V
Connections:	3 x 12x, 1 x 11x plug-in screw terminal for IOs - plug-in 1 x 4x, plug-in screw terminal for supply - plug-in 1 x RJ45 for network
Indicators:	Status LEDs for network 24 LEDs for digital statuses

Data transmission:

Protocols: HTTP and HTTPS
 TCP and UDP sockets, client and server
 MQTT - Publish and Subscribe
 REST
 SNMP V1 V2 V3 including traps
 SMTP e-mail sending
 OPC server
 Modbus TCP
 Inventory keeping, group management
 Response times: Data and switching traffic: typically 20 ms

Housing and other data:

Housing: Plastic housing for top hat rail installation
 90x116x56 mm (LxWxH)
 Enclosure rating: IP20
 Weight: approx. 250 g
 Storage temperature: -25°C - 70°C
 Operating temperature: 0°C - 60°C
 Permissible relative humidity: 5..95% RH (non-condensing)
 Scope of delivery: 1 x Web-IO 4.0 Digital, 12xIn, 8xRelay Out
 1 x Quick Guide
 Power supply and other accessories can be ordered separately

Accessories

*Net unit price for commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	21.00 €
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00 €
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	33.00 €

Storage and Visualization

logic.hub	50506	598.00 €
-----------	-----------------------	----------

Coupling relay for up to 230V

230V coupling relay - 1 x changeover for DIN rail mount	57015	22.00 €
230V coupling relay - 2 x changeover for DIN rail mount	57016	22.00 €

Mechanical Accessories

19" DIN rail	58813	21.00 €
Wall mount housing, enclosure rating IP66 / IP67	11120	54.00 €

Supplementary network products

Ethernet Switch Gigabit Industry, 4 Ports	55614	148.00 €
---	-----------------------	----------

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.



We are available to you in person:

W&T

www.WuT.de

Wiesemann & Theis GmbH

Porschestra. 12

42279 Wuppertal

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)

Fax: +49 202/2680-265

info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.