SIEMENS

Data sheet 3VL4140-2KE30-0AA0



circuit breaker VL400 UL; type JG (cat no. HJS3S400) non-interchangeable frame, with circuit breaker approval acc. to UL 489 high breaking capacity 3-pole, NEMA rating 65kA/480V, (molded case switch) Electronic Trip Unit magnetic TA=40°C In=< 400A, rated current II=4400A short-circuit protection non-auto. air circuit breaker without connection accessories without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	5.7 kg
Net Weight	5.7 kg

Approvals / Certificates

Environment		General Product Approval			Test Certificates
Environmental Confirmations	Environmental Confirmations	EAC	Confirmation	UKCA	Special Test Certificate

other

产品合格 QC PASS	Confirmation	Miscellaneous

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL4140-2KE30-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL4140-2KE30-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL4140-2KE30-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL4140-2KE30-0AA0





last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens