SIEMENS

Data sheet 6DL1134-6AF00-0PH1



SIMATIC ET 200SP HA, analog input module, AI 8xU/I/TC/4xRTD 2-/3-/4-wire HA suitable for terminal block, H1, N0, H0 color code CC00, channel diagnostics

General information	
Product type designation	AI 8xU/I/TC/4xRTD 2/3/4-wire HA
Firmware version	V1.0
● FW update possible	Yes
Usable terminal block	type H1, N0, H0 (see system manual for details)
Color code for module-specific color-coded label	CC00
Product function	
● I&M data	Yes; I&M0 to I&M3
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V18
● STEP 7 configurable/integrated from version	V5.6
● PCS 7 configurable/integrated from version	V9.1 SP2
● PCS neo can be configured/integrated from version	V4.0
● PROFINET from GSD version/GSD revision	GSDML V2.42 2023.01
Redundancy	
● Redundancy capability	No
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	220 mA
Encoder supply	
24 V encoder supply	
● 24 V	Yes
● Short-circuit protection	Yes; a max. of 1 channel may be operated in short-circuit
● Output current per channel, max.	0.032 A; max. 1 channel
Power loss	
Power loss, typ.	1.95 W
Address area	
Address space per module	
● Address space per module, max.	32 byte; + 2 bytes for QI information
Analog inputs	
Number of analog inputs	
● For current measurement	8
● For voltage measurement	8

Subject to change without notice
© Copyright Siemens

● For resistance/resistance thermometer measurement	4
● For thermocouple measurement	8
permissible input voltage for voltage input (destruction limit), max.	24 V
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	1.25 mA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
● 0 to +10 V	Yes; 15 bit
— Input resistance (0 to 10 V)	100 kΩ
● 1 V to 5 V	Yes; 15 bit
— Input resistance (1 V to 5 V)	100 kΩ
● -1 V to +1 V	Yes; 16 bit incl. sign
— Input resistance (-1 V to +1 V)	10 MΩ
● -10 V to +10 V	Yes; 16 bit incl. sign
— Input resistance (-10 V to +10 V)	100 kΩ
● -2.5 V to +2.5 V	Yes; 16 bit incl. sign
— Input resistance (-2.5 V to +2.5 V)	100 kΩ
● -250 mV to +250 mV	Yes; 16 bit incl. sign
— Input resistance (-250 mV to +250 mV)	10 MΩ
● -5 V to +5 V	Yes; 16 bit incl. sign
— Input resistance (-5 V to +5 V)	100 kΩ
● -50 mV to +50 mV	Yes; 16 bit incl. sign
— Input resistance (-50 mV to +50 mV)	10 MΩ
● -500 mV to +500 mV	Yes; 16 bit incl. sign
— Input resistance (-500 mV to +500 mV)	10 MΩ
● -80 mV to +80 mV	Yes; 16 bit incl. sign
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	50 Ω
● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	50 Ω
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	50 Ω
Input ranges (rated values), thermocouples	
● Type B	Yes; 16 bit incl. sign
— Input resistance (Type B)	10 MΩ
● Type C	Yes; 16 bit incl. sign
— Input resistance (Type C)	10 MΩ
● Type E	Yes; 16 bit incl. sign
— Input resistance (Type E)	10 MΩ
● Type J	Yes; 16 bit incl. sign
— Input resistance (type J)	10 MΩ
● Type K	Yes; 16 bit incl. sign
— Input resistance (Type K)	10 MΩ
● Type L	Yes; 16 bit incl. sign
— Input resistance (Type L)	10 MΩ
● Type N	Yes; 16 bit incl. sign
— Input resistance (Type N)	10 MΩ
● Type R	Yes; 16 bit incl. sign
— Input resistance (Type R)	10 MΩ
● Type S	Yes; 16 bit incl. sign
— Input resistance (Type S)	10 MΩ
● Type T	Yes; 16 bit incl. sign
— Input resistance (Type T)	10 MΩ
● Type U	Yes; 16 bit incl. sign
— Input resistance (Type U)	10 MΩ

© Copyright Siemens

● Type TXK/TXK(L) to GOST	Yes; 16 bit incl. sign
— Input resistance (Type TXK/TXK(L) to GOST)	10 MΩ
Input ranges (rated values), resistance thermometer	
● Cu 10	Yes; 16 bit incl. sign
— Input resistance (Cu 10)	10 MΩ
● Cu 50	Yes; 16 bit incl. sign
— Input resistance (Cu 50)	10 MΩ
● Cu 100	Yes; 16 bit incl. sign
— Input resistance (Cu 100)	10 MΩ
● Ni 100	Yes; 16 bit incl. sign
— Input resistance (Ni 100)	10 MΩ
● Ni 1000	Yes; 16 bit incl. sign
— Input resistance (Ni 1000)	10 MΩ
● LG-Ni 1000	Yes; 16 bit incl. sign
— Input resistance (LG-Ni 1000)	10 MΩ
● Ni 120	Yes; 16 bit incl. sign
— Input resistance (Ni 120)	10 MΩ
● Ni 200	Yes; 16 bit incl. sign
— Input resistance (Ni 200)	10 MΩ
● Ni 500	Yes; 16 bit incl. sign
— Input resistance (Ni 500)	10 MΩ
● Pt 100	Yes; 16 bit incl. sign
— Input resistance (Pt 100)	10 MΩ
● Pt 1000	Yes; 16 bit incl. sign
— Input resistance (Pt 1000)	10 MΩ
● Pt 200	Yes; 16 bit incl. sign
— Input resistance (Pt 200)	10 MΩ
● Pt 500	Yes; 16 bit incl. sign
— Input resistance (Pt 500)	10 MΩ
Input ranges (rated values), resistors	
● 0 to 150 ohms	Yes; 15 bit
— Input resistance (0 to 150 ohms)	10 MΩ
● 0 to 300 ohms	Yes; 15 bit
— Input resistance (0 to 300 ohms)	10 MΩ
● 0 to 600 ohms	Yes; 15 bit
— Input resistance (0 to 600 ohms)	10 MΩ
● 0 to 3000 ohms	Yes; 15 bit
— Input resistance (0 to 3000 ohms)	10 MΩ
● 0 to 6000 ohms	Yes; 15 bit
— Input resistance (0 to 6000 ohms)	10 MΩ
● PTC	Yes; 15 bit
— Input resistance (PTC)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— Parameterizable	Yes
— external temperature compensation via RTD	Yes
— Reference channel of the module	Yes; channel 7
— internal comparison point	Yes; with terminal block H1
— Reference channel of the group	Yes
— Number of reference channel groups	4
— fixed reference temperature	Yes
Cable length	
● shielded, max.	thermocouples: shielded cable length max. 200 m, voltages: shielded cable length max. 600 m, loop resistance max 8 kOhm; measuring ranges RTD: shielded cable length max. 600 m, cable resistance (single) max. 75 ohm, current measurement: shielded cable length max. 800 m
● unshielded, max.	200 m; Only applies when connecting current sensors
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	

Subject to change without notice
© Copyright Siemens

● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes; Channel-by-channel, results from the selected interference frequency suppression
● Interference voltage suppression for interference frequency f1 in Hz	10 / 50 / 60 / 400 Hz
● Conversion time (per channel)	Channel-by-channel, results from the selected interference frequency suppression
Smoothing of measured values	
● parameterizable	Yes; none, weak, medium, strong, channel-by-channel
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
● for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	820 Ω
● for current measurement as 4-wire transducer	Yes
● for resistance measurement with two-wire connection	Yes; all measuring ranges incl. PTC
● for resistance measurement with three-wire connection	Yes; All measuring ranges except PTC; internal compensation of the cable resistances
● for resistance measurement with four-wire connection	Yes; All measuring ranges except PTC
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.01 %; ±0.1 % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.002 %/K; ±0.005 % / K at thermocouple
Crosstalk between the inputs, min.	50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.3 %
● Current, relative to input range, (+/-)	0.3 %
● Resistance, relative to input range, (+/-)	0.3 %
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.1 %
● Current, relative to input range, (+/-)	0.1 %
● Resistance, relative to input range, (+/-)	0.1 %
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	60 dB
● Common mode voltage, max.	15 V
● Common mode interference, min.	90 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
● Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; channel-by-channel current 4 ... 20 mA, R and RTD
● Short-circuit	Yes; channel by channel for current (2-wire)
● Overflow/Underflow	Yes; channel by channel
Diagnostics indication LED	
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Permissible potential difference	

Subject to change without notice
© Copyright Siemens

between the inputs (UCM)	15 V DC/10 V AC
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	150 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596

Approvals / Certificates

General Product Approval

General Product Approval | **For use in hazardous locations**

Manufacturer Declaration

Declaration of Conformity

For use in hazardous locations | **Maritime application**

Miscellaneous

Maritime application | **Environment**

CCS (China Classification Society)

Subject to change without notice
© Copyright Siemens

last modified:	2/11/2026

Subject to change without notice
© Copyright Siemens