SIEMENS

Data sheet 6AV7881-3AE00-4DA0

	No longer available SIMATIC IPC277D (Nanopanel PC) 12" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 3x USB V2.0 (high current); 1x serial (COM 1); CompactFlash slot; 24 V DC power supply ATOM E660 (1.3 GHz), 2 GB RAM standard front 16 GB SIMATIC PC CompactFlash WES 7 SP1 (CF 4 GB or more/SSD) without SIMATIC software
General information	
Product type designation	IPC277D
Display	
Design of display	12" TFT touch
Screen diagonal	12 in
Resolution (pixels)	
● Horizontal image resolution	1 280 pixel
● Vertical image resolution	800 pixel
Backlighting	
● MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Keyboard	
● Function keys	No
● alphanumeric keyboard	No
Touch operation	
● Design as touch screen	Yes
Installation type/mounting	
Design	Panel PC, built-in unit
central design	Yes
distributed design	No
Mounting in portrait format possible	Yes
Supply voltage	
Type of supply voltage	24 V DC
Mains buffering	
● Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Intel Atom E6x0
Drives	
Optical drives	possible as external drive via USB
Hard disk	CF or SSD
SSD	Yes; ≥ 240 GB optional
Storage	
Main memory	1 GB to 2 GB
Capacity of main memory, max.	2 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	128 kbyte
Hardware configuration	
Slots	
● Number of compact flash slots	1; CompactFlash
Interfaces	
serial interface	COM1 (RS 232)
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Interrupts/diagnostics/status information	
LED status display	No

Subject to change without notice
© Copyright Siemens

Integrated Functions	
Monitoring functions	
● Temperature monitoring	Yes
● Fan	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
Marine approval	
● Germanischer Lloyd (GL)	Yes; 7", 9", 12"
● American Bureau of Shipping (ABS)	Yes; 7", 9", 12"
● Bureau Veritas (BV)	Yes; 7", 9", 12"
● Det Norske Veritas (DNV)	Yes; 7", 9", 12"
● Lloyds Register of Shipping (LRS)	Yes; 7", 9", 12"
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	50 °C; 19": max. 45 °C
Operating systems	
pre-installed operating system	
● Windows XP Professional	No
● Windows 7	No
Dimensions	
Width of the housing front	330 mm
Height of housing front	241 mm
Mounting cutout, width	310 mm
Mounting cutout, height	221 mm
mounting depth	66 mm
Weights	
Weight, approx.	2.75 kg

Approvals / Certificates

General Product Approval

Manufacturer Declaration

Manufacturer Declaration

General Product Approval | **Maritime application**

CCS (China Classification Society) | KR (Korean Register of Shipping)

Dangerous goods | **Environment**

Dangerous goods information | Test Summary Report UN 38.3 | Environmental Confirmations | Environmental Confirmations

last modified: 6/11/2026

Subject to change without notice
© Copyright Siemens