SIEMENS

Data sheet 6DL1131-6DF00-0PK0



SIMATIC ET 200SP HA, digital input module, DI 8X24 ... 125VDC HA suitable for terminal block K0, color code CC42, channel diagnostics

General information	
Product type designation	DI 8x24 ... 125 V DC HA
Firmware version	V1.0
● FW update possible	Yes
Usable terminal block	type K0 (see system manual for details)
Color code for module-specific color-coded label	CC42
Product function	
● I&M data	Yes; I&M0 to I&M3
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V16
● STEP 7 configurable/integrated from version	V5.6
● PCS 7 configurable/integrated from version	V9.0
● PCS neo can be configured/integrated from version	V3.0
● PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
● DI	Yes
● Counter	No
● Oversampling	No
● MSI	No
Redundancy	
● Redundancy capability	No
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	16 mA
Current consumption, max.	20 mA
Power loss	
Power loss, typ.	3.75 W
Address area	
Address space per module	
● Address space per module, max.	1 byte; + 1 byte for QI information
Digital inputs	
Number of digital inputs	8

Subject to change without notice
© Copyright Siemens

Sourcing/sinking input	Yes; P-reading		
Input characteristic curve in accordance with IEC 61131, type 1	Yes		
Input characteristic curve in accordance with IEC 61131, type 3	Yes		
Time stamp	Yes; Resolution 10 ms		
Time stamp (with precision of 1 ms)	Yes; Resolution 1ms		
Input voltage			
● for signal "0"	-125 ... +5 V		
● for signal "1"	+11 ... +125 V		
Input current			
● for signal "1", typ.	3.1 mA		
Input delay (for rated value of input voltage)			
for standard inputs			
— parameterizable	Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 µs, depending on line length)		
Cable length			
● shielded, max.	1 000 m		
● unshielded, max.	600 m		
Encoder			
Connectable encoders			
● 2-wire sensor	Yes		
— permissible quiescent current (2-wire sensor), max.	1.5 mA		
Interrupts/diagnostics/status information			
Alarms			
● Diagnostic alarm	Yes		
● Hardware interrupt	Yes; Parameterizable, channels 0 to 7, rising/falling edge		
Diagnoses			
● Diagnostic information readable	Yes		
● Monitoring the supply voltage	Yes		
● Wire break	Yes; channel by channel		
● Group error	Yes		
Diagnostics indication LED			
● MAINT LED	Yes; Yellow LED		
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED		
● Channel status display	Yes; green LED		
● for channel diagnostics	Yes; red LED		
● for module diagnostics	Yes; green/red DIAG LED		
Potential separation			
Potential separation channels			
● between the channels	No		
● between the channels and backplane bus	Yes		
Permissible potential difference			
between different circuits	250 V AC/300 V DC		
Isolation			
Isolation tested with	3 500 V DC/1 min, type test		
Ambient conditions			
Ambient temperature during operation			
● horizontal installation, min.	-40 °C		
● horizontal installation, max.	70 °C		
● vertical installation, min.	-40 °C		
● vertical installation, max.	60 °C		
Dimensions			
Width	22.5 mm		
Height	115 mm		
Depth	138 mm		
Weights			
Weight, approx.	165 g		
Classifications			
		Version	**Classification**

Subject to change without notice
© Copyright Siemens

eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599

Approvals / Certificates

General Product Approval

CE EG-Konf. | Miscellaneous | UKCA | Declaration of Conformity | KC | RCM

General Product Approval

EAC | China RoHS | Miscellaneous | CE EG-Konf. | UKCA | Manufacturer Declaration

For use in hazardous locations

IECEx | Declaration of Conformity | CCC | UL | ATEX | IECEx

For use in hazardous locations

Maritime application

Miscellaneous | ABS | Bureau Veritas | DNV | LRS | NK / Nippon Kaiji Kyokai

Maritime application

Environment

RINA | CCS (China Classification Society) | EPD | Siemens EcoTech

last modified: 2/11/2026

Subject to change without notice
© Copyright Siemens