SIEMENS

Data sheet 6GK5992-2VA00-8AA0

product type designation	**MM992-2VD (RJ45, variable distance)**
product description	XR-300 media module
	SCALANCE X accessory; Media module MM992-2VD; 2x 10/100/1000 Mbit/s RJ45 ports, electrical; with securing collar variable distance;



product brand name	SCALANCE
Technical Product Detail Page	https://i.siemens.com/1P6GK5992-2VA00-8AA0
suitability for use	Ethernet communication via two wire cable
suitability for operation	SCALANCE X308-2M, XR324-12M, S627-2M
interfaces	
number of electrical connections	
● for network components or terminal equipment / maximum	2
number of 10/100/1000 Mbit/s RJ45 ports	2
type of electrical connection	
● for network components or terminal equipment	RJ45
operating mode	
● standard Ethernet	Yes
● VD	Yes
wire length	
● for Standard Ethernet mode of operation / maximum	100 m
● of IE FC Standard Cable GP 4x2, AWG24, Cat6	
— at 100 Mbit/s / for VD mode of operation / maximum	500 m
● of IE FC Standard Cable GP 2x2, AWG22, Cat5e	
— at 10 Mbit/s / for VD mode of operation / maximum	500 m
— at 100 Mbit/s / for VD mode of operation / maximum	300 m
● of PB FC Standard Cable GP	
— at 10 Mbit/s / for VD mode of operation / maximum	1000 m
— at 100 Mbit/s / for VD mode of operation / maximum	100 m
ambient conditions	
ambient temperature	
● during operation	-40 ... +70 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Media module with retaining collar
width	60 mm
height	22 mm
depth	100 mm

Subject to change without notice
© Copyright Siemens

net weight	0.08 kg
fastening method	latched
● installation in media module slot	Yes
standards, specifications, approvals	
standard	
● for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4
● for hazardous zone	EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
● for hazardous zone / from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4
● for emitted interference	EN 61000-6-4:2007 (Class A)
● for interference immunity	EN 61000-6-2:2005
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
● CE marking	Yes
● C-Tick	Yes
● KC approval	Yes
● CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
● CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc
Marine classification association	
● French marine classification society (BV)	Yes
MTBF	250 a
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	56.15 kg
● during manufacturing	10.1 kg
● during operation	45.95 kg
● after end of life	0.1 kg
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
Approvals / Certificates	
General Product Approval	

Subject to change without notice
© Copyright Siemens

Declaration of Conformity | China RoHS | Manufacturer Declaration

General Product Approval	For use in hazardous locations

China RoHS | FM

For use in hazardous locations	Maritime application

CCC-Ex | NK / Nippon Kaiji Kyokai

Maritime application	Environment

last modified: 3/25/2026

Subject to change without notice
© Copyright Siemens