SIEMENS

## Data sheet 6AG1422-1BL00-2AA0



SIPLUS S7-400 SM 422 32DA based on 6ES7422-1BL00-0AA0 with conformal coating, -25…+60 °C,

| | |
|---|---|
| **General information** | |
| based on | 6ES7422-1BL00-0AA0 |
| **Supply voltage** | |
| Load voltage L+ | |
| ● Rated value (DC) | 24 V |
| ● permissible range, lower limit (DC) | 20.4 V |
| ● permissible range, upper limit (DC) | 28.8 V |
| **Input current** | |
| from load voltage L+ (without load), max. | 30 mA |
| from backplane bus 5 V DC, max. | 200 mA |
| **Power loss** | |
| Power loss, typ. | 4 W |
| **Digital outputs** | |
| Number of digital outputs | 32 |
| Short-circuit protection | Yes; Clocked electronically |
| ● Response threshold, typ. | 0.7 to 1.5 A |
| Limitation of inductive shutdown voltage to | -27 V |
| Controlling a digital input | Yes; possible |
| Switching capacity of the outputs | |
| ● on lamp load, max. | 5 W |
| Load resistance range | |
| ● lower limit | 48 Ω |
| ● upper limit | 4 kΩ |
| Output voltage | |
| ● for signal "1", min. | L+ (-0.3 V) |
| Output current | |
| ● for signal "1" rated value | 0.5 A |
| ● for signal "1" permissible range, min. | 5 mA |
| ● for signal "1" permissible range, max. | 0.6 A |
| ● for signal "0" residual current, max. | 0.3 mA |
| Output delay with resistive load | |
| ● "0" to "1", max. | 1 ms |
| ● "1" to "0", max. | 1 ms |
| Parallel switching of two outputs | |
| ● for uprating | Yes; possible (only outputs of the same group) |
| ● for redundant control of a load | Yes; possible (only outputs of the same group) |
| Switching frequency | |
| ● with resistive load, max. | 100 Hz |
| ● with inductive load, max. | 0.5 Hz |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● with inductive load (acc. to IEC 60947-5-1, DC13), max. | 2 Hz; 2 Hz at 0.3 A; 0.5 Hz at 0.5 A |
| ● on lamp load, max. | 10 Hz |
| Total current of the outputs (per group) | |
| all mounting positions | |
| — up to 40 °C, max. | 4 A |
| — up to 60 °C, max. | 2 A; 8 adjacent outputs each |
| Cable length | |
| ● shielded, max. | 1 000 m |
| ● unshielded, max. | 600 m |
| **Interrupts/diagnostics/status information** | |
| Diagnostics function | No |
| **Potential separation** | |
| Potential separation digital outputs | |
| ● between the channels | No |
| ● between the channels, in groups of | 32 |
| ● between the channels and backplane bus | Yes |
| **Isolation** | |
| Isolation tested with | 500 V AC/707 V DC, type test |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | -25 °C; = Tmin |
| ● max. | 60 °C; = Tmax |
| Ambient temperature during storage/transportation | |
| ● min. | -40 °C |
| ● max. | 70 °C |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 5 000 m |
| ● Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| ● With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions) |
| Resistance | |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| ● Coatings for printed circuit board assemblies acc. to EN 61086 | Yes; Class 2 for high reliability |
| ● Protection against fouling acc. to EN 60664-3 | Yes; Type 1 protection |
| ● Military testing according to MIL-I-46058C, Amendment 7 | Yes; Discoloration of coating possible during service life |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A |

**Dimensions**

| | |
|---|---|
| Width | 25 mm |
| Height | 290 mm |
| Depth | 210 mm |

**Weights**

| | |
|---|---|
| Weight, approx. | 600 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 16 | 27-24-22-04 |
| eClass | 14 | 27-24-22-04 |
| eClass | 12 | 27-24-22-04 |
| eClass | 9.1 | 27-24-22-04 |
| eClass | 9 | 27-24-22-04 |
| eClass | 8 | 27-24-22-04 |
| eClass | 7.1 | 27-24-22-04 |
| eClass | 6 | 27-24-22-04 |
| ETIM | 10 | EC001419 |
| ETIM | 9 | EC001419 |
| ETIM | 8 | EC001419 |
| ETIM | 7 | EC001419 |
| IDEA | 4 | 3566 |
| UNSPSC | 15 | 32-15-17-05 |

**Approvals / Certificates**

**General Product Approval**

CE EG-Konf. | Manufacturer Declaration | UKCA | EAC | China RoHS | UKCA

**EMV**

KC | RCM

**For use in hazardous locations**

CCC-Ex | IECEx | ATEX

**last modified:** 10/23/2025


Subject to change without notice
© Copyright Siemens