SIEMENS

Data sheet 6AG1960-1CB00-4AA5

SIPLUS S7-1500 sync submodule up to 200 m based on 6ES7960-1CB00-0AA5 with conformal coating, 0…+60 °C, for patch cable up to 200 m




Figure similar

General information	
Product type designation	Synchronization module
based on	6ES7960-1CB00-0AA5
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Power loss	
Power loss, typ.	0.77 W
Interfaces	
Optical interface	Yes
● design of optical connection	LC
● wavelength of optical interface	850 nm
● range (depending on optical fiber used), min.	1 m
● range (depending on optical fiber used), max.	200 m
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	0 °C; = Tmin
● horizontal installation, max.	60 °C; = Tmax
● vertical installation, min.	0 °C; = Tmin
● vertical installation, max.	40 °C
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *

Subject to change without notice
© Copyright Siemens

Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
● Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
● Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
● Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Dimensions	
Width	13 mm
Height	14 mm
Depth	58 mm
Weights	
Weight, approx.	18 g

Classifications

	Version	Classification
eClass	16	27-24-22-08
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

China RoHS

General Product Approval

last modified: 6/24/2025

Subject to change without notice
© Copyright Siemens