SIEMENS

## Data sheet 6AV7884-2AB10-3BB0

| | |
|---|---|
| | ***no longer available*** SIMATIC HMI IPC 477C optional bundle with WinCC flexible 2008/WinAC, 15" Touch display, 1024x 768; 4 USB (back)+1 USB (front) Standard front Celeron M 1.2 GHz, PROFINET (IE); 2x 1 Gbit; PROFIBUS DP 12 1 GB -RAM, DDR3; 2nd CF slot not equipped CF card: 4 GB Windows Embedded Standard 2009 pre-installed WinAC RTX |
| **Display** | |
| Design of display | 15" TFT touch |
| Screen diagonal | 15 in |
| Resolution (pixels) | |
| ● Horizontal image resolution | 1 024 pixel |
| ● Vertical image resolution | 768 pixel |
| Backlighting | |
| ● MTBF backlighting (at 25 °C) | 50 000 h |
| **Control elements** | |
| Input device | |
| ● Integrated mouse cursor control | No |
| Keyboard | |
| ● Function keys | No |
| — Number of function keys | 0 |
| ● alphanumeric keyboard | No |
| Touch operation | |
| ● Design as touch screen | Yes |
| **Installation type/mounting** | |
| central design | Yes |
| distributed design | No |
| **Supply voltage** | |
| Type of supply voltage | 24 V DC |
| **Processor** | |
| Processor type | Intel Celeron M 1.2 GHz, Intel Core2Solo 1.2 GHz or Intel Core2Duo 1.2 GHz |
| **Drives** | |
| Optical drives | possible as external drive via USB |
| Hard disk | Compact Flash Drive, without rotating parts or Solid State Drive with at least 32 GB can be selected using the Configurator |
| **Storage** | |
| Type of memory | DDR3-SDRAM |
| Main memory | 512 MB |
| Capacity of main memory, max. | 4 096 Mbyte; At least 3.2 GB can be used |
| **Data areas and their retentivity** | |
| Retentive data area (incl. timers, counters, flags), max. | 2 048 kbyte; 128 KB can be stored in the buffer time |
| **Hardware configuration** | |
| Slots | |
| ● Number of PCI slots | 0 |
| ● Number of compact flash slots | 2 |
| **Interfaces** | |
| serial interface | COM1: 1x V.24 (RS 232) |
| Video interfaces | |
| ● Graphics interface | DVI-I: VGA / DVI combined |
| Industrial Ethernet | |
| ● Industrial Ethernet interface | |
| — 100 Mbps | Yes |
| — 1000 Mbps | Yes |
| **Protocols** | |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| Protocols (Ethernet) | |
| ● TCP/IP | Yes |
| **Interrupts/diagnostics/status information** | |
| LED status display | No |
| **Integrated Functions** | |
| Monitoring functions | |
| ● Temperature monitoring | Yes |
| **Degree and class of protection** | |
| IP (at the front) | IP65 |
| **Standards, approvals, certificates** | |
| CE mark | Yes |
| Use in hazardous areas | |
| ● FM Class I Division 2 | No |
| Marine approval | |
| ● Germanischer Lloyd (GL) | Yes |
| ● American Bureau of Shipping (ABS) | Yes |
| ● Bureau Veritas (BV) | Yes |
| ● Det Norske Veritas (DNV) | Yes |
| ● Lloyds Register of Shipping (LRS) | Yes |
| ● Polski Rejestr Statkow (PRS) | Yes |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● min. | 0 °C |
| ● max. | 50 °C |
| Vibrations | |
| ● Vibration resistance during operation acc. to IEC 60068-2-6 | tested to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm, 58 Hz to 200 Hz: 9.8 m/s² (1 g) |
| **Operating systems** | |
| pre-installed operating system | Windows XP Prof. (Multi-Language), Windows XP embedded or optionally without operating system |
| without operating system | No |
| pre-installed operating system | |
| ● Windows XP Professional | Yes |
| **Dimensions** | |
| Width of the housing front | 483 mm |
| Height of housing front | 310 mm |
| Mounting cutout, width | 450 mm |
| Mounting cutout, height | 290 mm |
| mounting depth | 75 mm |
| **Weights** | |
| Weight, approx. | 7 kg |
| **Approvals / Certificates** | |

**General Product Approval**













| EMV | Maritime application | | | | |
|---|---|---|---|---|---|
|   |   |   | NK / Nippon Kaiji Kyokai | Miscellaneous | CCS (China Classification Society) |

**Dangerous goods**


Subject to change without notice
© Copyright Siemens

| | | | |
|---|---|---|---|
| Dangerous goods information | Test Summary Report UN 38.3 | Dangerous goods information | Test Summary Report UN 38.3 |

**last modified:** 4/2/2026


Subject to change without notice
© Copyright Siemens