SIEMENS

Data sheet 3NC1450



Figure similar

SITOR cylindrical fuse link, 14x51 mm, 50 A, aR, Un AC: 690 V, Un DC: 700 V, DC according to UL

Model	
product brand name	SENTRON
product designation	SITOR fuse link
design of the product	DC acc. to UL
General technical data	
operating class of the fuse link	aR
type of voltage of the operating voltage	AC
supply voltage at DC	700 V
Dissipation	
power loss [W]	9 W
power loss [W] for rated value of the current at AC in hot operating state per pole	9 W
Main circuit	
operational current rated value	50 A
Product details	
product component striker	No
Mechanical Design	
mounting position	Any, preferably vertical
Net Weight	21 g

Approvals Certificates

Environment		General Product Approval		
Environmental Confirmations	EPD	Environmental Confirmations	cURus	Confirmation


General Product Approval		other
CE EG-Konf.	UKCA	产品合格 QC PASS — Confirmation

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012

Subject to change without notice
© Copyright Siemens

Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1450
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3NC1450
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1450
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/3NC1450



last modified: 11/14/2025

© Copyright Siemens

Subject to change without notice
© Copyright Siemens