

Data sheet:

Web-IO 4.0 Digital, 2xIn, 2xOut



Article no.: 57737

338.00 €

*Net price for
commercial users

Switch, monitor and count ...

With the Web-IO 4.0 Digital [switching signals](#) can be controlled, acquired and monitored over TCP/IP Ethernet. Numerous web and network services are available for reporting changes on the inputs and outputs - even directly in a browser. With protocols such as [OPC UA](#), [MQTT](#) and [REST](#) the Web-IO is an ideal fit in the world of Industry 4.0 and the Internet of Things.

Properties

Switching signals:

- **2 switching inputs:**
 - Digital 24V inputs
 - 32-bit pulse counter
- **2 switching outputs:**
 - Digital 24V outputs
(12V, 48V, 110V, 230V via [coupling relays](#))
 - Drive up to 500mA
 - Short-circuit-protected

Wiring example

Connectivity:

- **Intuitive Web interface** for simpler operation
 - Select between German or English
 - [Switching the outputs directly from the Web interface](#)
 - [Adaptation for smartphone](#)
 - HTTP and HTTPS
- **Current Industry 4.0 protocols:**
 - [OPC UA](#), REST and [MQTT](#) support
 - AMQP on request
- **Box-to-Box**
 - [Pass switching signals over the network 1:1](#)
- **Alarm and reporting functions:**
 - [Email for alarm sending or as status report](#)
 - [SNMP polling / alarm traps V1 V2 V3](#)
 - Switching your outputs in alarm situations
 - Switching the outputs on another Web-IO
 - HTTP requests for controlling third-party devices
 - Up to 30 actions can be configured
- **Dynamic integration into other Web sites:**
 - Direct access to current IO states via [HTTP requests](#), [AJAX](#) and [JavaScript](#)
- **Additional software interfaces for incorporating into your systems/databases:**
 - [OPC UA](#), [OPC DA](#)
 - [Modbus TCP](#)
 - Syslog, SNMP V1 V2 V3

- TCP and UDP sockets, client and server
- HTTP, HTTPS, AJAX
- FTP (data logging)
- **Internal clock**
 - Time synchronization using time server calibration
 - Battery-backed device clock
- **Possible applications:**
 - Remote monitoring and fault messaging
 - Cross-location switching
 - House and building automation
 - Process monitoring and visualization
 - Light, gate and cabinet control
 - Machine Data Collection (MDC)
 - More uses can be found [here](#).

Power supply:

- **External**
 - Screw terminal
 - 12 - 48V DC
- **Power-over-Ethernet (PoE)**
 - Phantom power using data pairs
 - Power over unused wire pairs

Standards & more

- **Conforms to standards both in office and industrial environments:**
 - High noise resistance per EN 61000-6-2
 - Low noise emission per EN 55032:2015 + A1 Cl. B, EN 61000-3-2 & EN 61000-3-3
- **5 year guarantee**

Wish for something!

[Your suggestions for improvement and additions](#)

Technical data

Connections, displays and control elements:

Digital outputs:	2 x Digital Out 6V-30V, 500mA Grouping of 2 outputs Max. group current 1A Max. total current 1A Short-circuit-protected Using our coupling relays voltages of even up to 230V can be switched
Digital inputs:	2 x Digital In, max. input voltage +/-30V protected against reverse connection within this range Switching threshold 8V +/- 1.5V "On" current = 2.2 mA integrated 32-bit counter
Network:	10/100BaseT autosensing
Power supply:	Power-over-Ethernet (PoE) or 24-48V DC (approx. 100mA@24V)
Auxiliary power output:	24V max. 125mA for IO supply
Galvanic isolation:	Digital outputs - network: min. 1000 V Digital inputs - network: min. 2000 V Digital inputs - outputs: min. 1000 V
Adapters:	1 x 6x screw terminal for IOs - plug-in 1 x 2x screw terminal block for external power - plug-in 1 x RJ45 for network
Displays:	Status LEDs for network 4 LEDs for digital status

Data transmission:

Protocols: HTTP and HTTPS
 TCP and UDP sockets, client and server
 MQTT - Publish and Subscribe
 REST
 SNMP V1 V2 V3 including traps
 SMTP e-mail sending
 OPC server
 Modbus TCP
 Inventory keeping, group management

Response times: Data and switching traffic: typically 12 ms

Housing and other data:

Housing: Plastic housing for top hat rail installation
 105x22x75mm (LxWxH)
 Enclosure rating: IP20
 Weight: approx. 140 g
 Storage temperature: -25°C - 70°C
 Operating temperature: 0°C - 60°C
 Permissible relative humidity: 5..95% RH (non-condensing)
 Scope of delivery: 1 x Web-IO 4.0 Digital, 2xIn, 2xOut
 1 x Quick Guide
 Power supply and other accessories can be ordered separately

Accessories

*Net unit price for
 commercial users

Power supplies

Plug-in power supply, 24V / 500mA DC with Euro plug	11021	21.00 €
Plug-in Power Supply, 24V / 750mA DC with Euro, US and UK plug	11026	38.00 €
Power supply for DIN rail, 24V / 630mA DC (merchandise, 2-year manufacturer's guarantee)	11080	33.00 €

Coupling relay for up to 230V

230V coupling relay - 1 x changeover for DIN rail mount	57015	22.00 €
230V coupling relay - 2 x changeover for DIN rail mount	57016	22.00 €

Mechanical Accessories

Mounting bracket for wall mounting	58812	11.20 €
19" DIN rail	58813	21.00 €
Wall mount housing, enclosure rating IP66 / IP67	11120	54.00 €

Supplementary network products

Ethernet Switch Gigabit Industry, 4 Ports	55614	148.00 €
logic.hub	50506	598.00 €

Software

Web-IO2Go (app for iOS)	57700	free
-------------------------	-----------------------	------

* Our offering is intended only for commercial users. We will be happy to refer private end customers to trading partners through whom our products can be purchased.

Secure connection:



We are available to you in person:

W&T

www.WuT.de

Wiesemann & Theis GmbH
Porschestr. 12
42279 Wuppertal

Phone: +49 202/2680-110 (Mon.-Fri. 8 a.m. to 5 p.m.)

Fax: +49 202/2680-265

info@wut.de

© Wiesemann & Theis GmbH, subject to mistakes and changes: Since we can make mistakes, none of our statements should be applied without verification. Please let us know of any errors or misunderstandings you find so that we can become aware of and eliminate them.