SIEMENS

Data sheet 6ES7332-8TF01-0AB0



Figure similar

********** spare part ********* SIMATIC DP, HART analog output, SM 332, 8 AO, 0/4 - 20 mA HART for ET200M with IM153-2, IM 153-2, 20-pole functions: firmware update, HART auxiliary variables, redundancy, local diagnostic buffer with time stamping,

General information	
Product function	
● Isochronous mode	No
Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	350 mA
from backplane bus 5 V DC, max.	110 mA
Power loss	
Power loss, typ.	6 W
Analog outputs	
Number of analog outputs	8
Current output, no-load voltage, max.	24 V
Output ranges, current	
● 0 to 20 mA	Yes
● -20 mA to +20 mA	No
● 4 mA to 20 mA	Yes
Connection of actuators	
● for current output two-wire connection	Yes
Load impedance (in rated range of output)	
● with current outputs, max.	750 Ω
● with current outputs, inductive load, max.	10 mH
Destruction limits against externally applied voltages and currents	
● Voltages at the outputs towards MANA	+60/-0.5 V
Cable length	
● shielded, max.	800 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Basic execution time of the module (all channels released)	10 ms; 10 ms in AO mode 50 ms in HART-AO mode
Settling time	
● for resistive load	0.1 ms
● for inductive load	0.5 ms
Errors/accuracies	
Operational error limit in overall temperature range	

Subject to change without notice
© Copyright Siemens

● Current, relative to output range, (+/-)	0.2 %
Basic error limit (operational limit at 25 °C)	
● Current, relative to output range, (+/-)	0.1 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog outputs	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	500 V DC
Degree and class of protection	
IP degree of protection	IP20
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	220 g

Classifications

	Version	Classification
eClass	16	27-24-26-01
eClass	14	27-24-26-01
eClass	12	27-24-26-01
eClass	9.1	27-24-26-01
eClass	9	27-24-26-01
eClass	8	27-24-26-01
eClass	7.1	27-24-26-01
eClass	6	27-24-26-01
ETIM	10	EC001596
ETIM	9	EC001596
ETIM	8	EC001596
ETIM	7	EC001596
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

General Product Approval	For use in hazardous locations

Subject to change without notice
© Copyright Siemens

China RoHS | Miscellaneous | FM

ATEX | IECEx

For use in hazardous locations	Maritime application

CCC-Ex | Miscellaneous

CCC | UL | IECEx | ABS

Maritime application

NK / Nippon Kaiji Kyokai

DNV | PRS

last modified: 7/16/2026

Subject to change without notice
© Copyright Siemens