SIEMENS

# Data sheet for Line filter

## Article No. : 6SL3203-0BE23-8BA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Rated data | |
|---|---|
| **Input** | |
| Number of phases | 3 AC |
| Line voltage | 380 ... 480 V |
| **Output** | |
| Rated current | 49.4 A |

| Mechanical data | |
|---|---|
| Degree of protection | IP20 / UL open type |
| Net weight | 7.30 kg (16.09 lb) |
| **Dimensions** | |
| Width | 140.0 mm (5.51 in) |
| Height | 359.0 mm (14.13 in) |
| Depth | 95.0 mm (3.74 in) |

| Connections | |
|---|---|
| **Line side** | |
| Version | screw-type terminal |
| Conductor cross-section | 6.00 ... 16.00 mm² (AWG 10 ... AWG 6) |
| **Load side** | |
| Version | shielded lead |
| Conductor cross-section | 10.00 mm² (AWG 8) |
| Cable length | 0.54 m (1.77 ft) |
| **PE connection** | |
| Version | On housing with M6 screw studs |

Subject to change. Calculated values may differ from nameplate ratings. © Copyright Siemens