SIEMENS

## Data sheet 6AV7260-2GM32-1XA3

SIMATIC IPC677D (Panel PC), 2x10/100/1000 Mbit/s Ethernet; 4x USB V3.0, 1x serial (COM1); Watchdog, temperature and Fan monitoring; RAID controller onboard; 22" Touch (1920x 1080); with front USB XEON E3-1268LV3 (4C/8T, 2.3 (3.3) GHz, 8 MB cache VT-D, AMT) Solid-state drive 240 GB 8 GB DDR3 1600 DIMM; 1x PCIE (X16); 1x PCIE (X4) 2x USB additive (1 slot occupied) without operating system SIMATIC IPC DiagMonitor enclosed AC 110/230V industrial power supply unit with NAMUR; Power supply cable USA

| | |
|---|---|
| **Display** | |
| Design of display | 22" TFT touch |
| Screen diagonal | 22 in |
| Resolution (pixels) | |
| ● Horizontal image resolution | 1 920 pixel |
| ● Vertical image resolution | 1 080 pixel |
| Backlighting | |
| ● MTBF backlighting (at 25 °C) | 30 000 h |
| **Control elements** | |
| Touch operation | |
| ● Design as touch screen | Yes; analog, resistive |
| **Installation type/mounting** | |
| Mounting | For horizontal and vertical mounting |
| Design | Panel PC, built-in unit |
| central design | Yes |
| Mounting in portrait format possible | Yes |
| **Supply voltage** | |
| Type of supply voltage | 100/240 V AC (autorange); 24 V DC |
| Line frequency | |
| ● Rated value 50 Hz | Yes |
| ● Rated value 60 Hz | Yes |
| Mains buffering | |
| ● Mains/voltage failure stored energy time | 10 ms |
| **Processor** | |
| Processor type | Celeron G1820TE (2C/2T, 2.2 GHz, 2 MB Cache); Core i3-4330TE (2C/4T, 2.4 GHz, 4 MB Cache); Xeon E3-1268L v3 (4C/8T, 2.3 (3.3) GHz, 8 MB Cache, AMT) |
| Chipset | Intel DH82C226 PCH |
| **Graphic** | |
| Graphics controller | Intel HD graphics controller P4600 GT2 (Xeon, Core i3); Intel HD graphics controller (Celeron) |
| **Drives** | |
| Optical drives | DVD±R±RW combi-drive, optional |
| Hard disk | 3.5" SATA ≥ 500 GB, optional: 3.5" SATA ≥ 1 TB; RAID1 2x 2.5" SATA ≥ 320 GB; solid-state drive (SSD) ≥ 240 GB; all hard disk drives within the enclosure are vibration-damped; RAID1 2x 2.5" SATA ≥ 320 GB byte in removable drive bay |
| SSD | Yes; ≥ 240 GB optional |
| **Storage** | |
| Type of memory | DDR3-1600 DIMM |
| Main memory | 2 / 4 / 8 / 16 GB; ECC optional |
| Capacity of main memory, max. | 16 Gbyte |
| **Data areas and their retentivity** | |
| Retentive data area (incl. timers, counters, flags), max. | 2 Mbyte; 128 KB can be stored in the buffer time; optional |
| **Hardware configuration** | |
| Slots | |
| ● Number of PCI slots | 2 |


Subject to change without notice
© Copyright Siemens

| | | | |
|---|---|---|---|
| ● Number of PCI slots | 2 | | |
| **Interfaces** | | | |
| Number of industrial Ethernet interfaces | 2; 2x RJ45 (independent) | | |
| Number of PROFINET interfaces | 3; Optional | | |
| serial interface | 1x COM1 (RS 232), optional: 1x COM2 (RS 232) | | |
| Video interfaces | | | |
| ● Graphics interface | 1x DisplayPort and 1x DVI-I; 1x VGA via adapter cable (optional) | | |
| Industrial Ethernet | | | |
| ● Industrial Ethernet interface | | | |
| — 100 Mbps | Yes | | |
| — 1000 Mbps | Yes | | |
| **Interrupts/diagnostics/status information** | | | |
| LED status display | Yes | | |
| Bus diagnostics | Yes | | |
| **Integrated Functions** | | | |
| Monitoring functions | | | |
| ● Temperature monitoring | Yes | | |
| ● Fan | Yes | | |
| ● Monitoring function via network | Optional | | |
| **Degree and class of protection** | | | |
| IP degree of protection | IP20 | | |
| IP (at the front) | IP65 | | |
| IP (rear) | IP20 | | |
| **Standards, approvals, certificates** | | | |
| CE mark | Yes | | |
| UL approval | Yes | | |
| ● UL 508 | Yes | | |
| cULus | Yes | | |
| RCM (formerly C-TICK) | Yes | | |
| KC approval | Yes | | |
| FCC | Yes | | |
| **Ambient conditions** | | | |
| Ambient temperature during operation | | | |
| ● min. | 5 °C | | |
| ● max. | 45 °C | | |
| Ambient temperature during storage/transportation | | | |
| ● min. | -20 °C | | |
| ● max. | 60 °C | | |
| Vibrations | | | |
| ● Vibration resistance during operation acc. to IEC 60068-2-6 | tested according to DIN IEC 60068-2-6: 10 Hz to 58 Hz: 0.075 mm; 58 Hz to 500 Hz 9.8 m/s² (1 g) | | |
| **Operating systems** | | | |
| pre-installed operating system | Windows 7 Ultimate, 32-bit/64-bit, MUI; Windows Embedded Standard 7 P, 32-bit, MUI; Windows 10 Enterprise 2015 or 2016 LTSB, 64-bit, MUI | | |
| without operating system | Yes | | |
| pre-installed operating system | | | |
| ● Windows 7 | Yes; Ultimate 32 bit or 64 bit | | |
| ● Windows 10 Enterprise | Yes; Windows 10 Enterprise 2015 or 2016 LTSB, 64-bit, MUI | | |
| **Dimensions** | | | |
| Width of the housing front | 560 mm | | |
| Height of housing front | 380 mm | | |
| Mounting cutout, width | 542 mm | | |
| Mounting cutout, height | 362 mm | | |
| mounting depth | 112 mm | | |
| **Weights** | | | |
| Weight, approx. | 16 kg | | |
| **Classifications** | | | |
| | | **Version** | **Classification** |


Subject to change without notice
© Copyright Siemens

| | | |
|---|---|---|
| eClass | 16 | 19-20-01-03 |
| eClass | 14 | 19-20-01-03 |
| eClass | 12 | 19-20-01-03 |
| eClass | 9.1 | 19-20-01-03 |
| eClass | 9 | 19-20-01-03 |
| eClass | 8 | 27-24-23-01 |
| eClass | 7.1 | 27-24-23-01 |
| eClass | 6 | 27-24-23-01 |
| ETIM | 10 | EC001414 |
| ETIM | 9 | EC001414 |
| ETIM | 8 | EC001414 |
| ETIM | 7 | EC001414 |

## Approvals / Certificates

### General Product Approval

Miscellaneous

Manufacturer Declaration

### General Product Approval

BIS CRS

China RoHS

### Dangerous goods

Dangerous goods information

Test Summary Report UN 38.3

Dangerous goods information

Test Summary Report UN 38.3

### Environment

Environmental Confirmations

Environmental Confirmations

**last modified:** 6/11/2026


Subject to change without notice
© Copyright Siemens