SIEMENS

Data sheet 6AV7885-5AA10-1DA1

	no longer available SIMATIC HMI IPC 577C PCI slot, 4 USB (back)+1 USB (front), Ethernet (10/100/1000), 19" touch display ; Celeron M 1.2 GHz, PROFINET (IE); 2x 1 Gbit 1 GB -RAM, DDR3; 2nd mass storage: Not equipped 1st mass storage (Operating system optional): 320 GB HDD SATA WinXP Prof. pre-installed (only possible with HD or SSD) without expansion (software) 110/230 V AC power supply unit with NAMUR,
Display	
Design of display	19" TFT touch
Screen diagonal	19 in
Resolution (pixels)	
● Horizontal image resolution	1 280 pixel
● Vertical image resolution	1 024 pixel
Backlighting	
● MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
● Integrated mouse cursor control	No
Keyboard	
● Function keys	No
— Number of function keys	0
● alphanumeric keyboard	No
Touch operation	
● Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Supply voltage	
Type of supply voltage	110/230 V AC or 24 V DC
Processor	
Processor type	Intel Celeron M 1.2 GHz, Intel Core2Solo 1.2 GHz, Intel Core2Duo 1.86 GHz
Drives	
Optical drives	Optional: DVD±R±RW combi drive; on rear, can be operated from side
Hard disk	3.5" SATA hard disk ≥ 80 GB, vibration-resistant mounting
Storage	
Type of memory	DDR3-SDRAM
Main memory	512 MB
Capacity of main memory, max.	4 096 Mbyte; At least 3.2 GB can be used
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	2 048 kbyte; 128 KB can be stored in the buffer time
Hardware configuration	
Slots	
● Number of PCI slots	1
● Number of compact flash slots	1
Interfaces	
serial interface	COM1: 1x V.24 (RS 232)
Video interfaces	
● Graphics interface	DVI-I: VGA / DVI combined
Industrial Ethernet	
● Industrial Ethernet interface	
— 100 Mbps	Yes
— 1000 Mbps	Yes
Protocols	

Subject to change without notice
© Copyright Siemens

Protocols (Ethernet)	
● TCP/IP	Yes
Interrupts/diagnostics/status information	
LED status display	No
Integrated Functions	
Monitoring functions	
● Temperature monitoring	Yes
Degree and class of protection	
IP (at the front)	IP65
Standards, approvals, certificates	
CE mark	Yes
Use in hazardous areas	
● FM Class I Division 2	No
Marine approval	
● Germanischer Lloyd (GL)	No
● American Bureau of Shipping (ABS)	No
● Bureau Veritas (BV)	No
● Det Norske Veritas (DNV)	No
● Lloyds Register of Shipping (LRS)	No
● Polski Rejestr Statkow (PRS)	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	50 °C
Vibrations	
● Vibration resistance during operation acc. to IEC 60068-2-6	Mech. environmental conditions tested in acc. with IEC 60068-2-6 Vibration: in operation with CompactFlash Card and SSD: 10 Hz to 58 Hz: 0.075 mm, 58 Hz to 500 Hz: 9.8 m/s²; in operation with HDD: 10 Hz to 58 Hz: 0.0375 mm, 58 Hz to 500 Hz: 4.9 m/s²
Operating systems	
pre-installed operating system	Windows XP Embedded and Win XP Prof.
without operating system	Yes
pre-installed operating system	
● Windows XP Professional	Yes; Only with SSD or HDD
Dimensions	
Width of the housing front	483 mm
Height of housing front	400 mm
Mounting cutout, width	450 mm
Mounting cutout, height	380 mm
mounting depth	125 mm
Weights	
Weight, approx.	11.6 kg
Approvals / Certificates	
General Product Approval	

EMV	Dangerous goods			
RCM	Dangerous goods information	Test Summary Report UN 38.3	Dangerous goods information	Test Summary Report UN 38.3

last modified: 4/2/2026

Subject to change without notice
© Copyright Siemens