SIEMENS

Data sheet 6ES7132-6BH60-0AA0



SIMATIC ET 200SP, digital output module, DQ 16x24 V DC/0.5 A SNK BA, sink output (NPN, sourcing) packing unit: 1 unit, suitable for BU type A0, color code CC00, substitute value output, module diagnostics for: supply voltage

General information	
Product type designation	DQ 16x24VDC/0.5A SNK BA
Firmware version	V0.0
● FW update possible	No
usable BaseUnits	BU type A0
Color code for module-specific color-coded label	CC00
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	STEP 7 V19 or higher with HSP0433, integrated as of V21
● PROFIBUS from GSD version/GSD revision	One GSD file each, Revision 3 and 5 and higher
● PROFINET from GSD version/GSD revision	GSDML V2.43
Operating mode	
● DQ	Yes
● DQ with energy-saving function	No
● PWM	No
● Oversampling	No
● MSO	No
Redundancy	
● Redundancy capability	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	30 mA; rated voltage, all channels active, no load
Current consumption, max.	8 A; worst case voltage, all channels active, max. load, no derating
Output voltage	
Rated value (DC)	24 V
Power loss	
Power loss, typ.	1.5 W; rated voltage, 50 % active channels
Address area	
Address space per module	
● Address space per module, max.	2 byte
● Outputs	2 byte
Hardware configuration	
Automatic encoding	Yes

Subject to change without notice
© Copyright Siemens

● Mechanical coding element	Yes
● Type of mechanical coding element	Type A
Selection of BaseUnit for connection variants	
● 1-wire connection	BU type A0
● 2-wire connection	BU type A0 with AUX terminals or potential distributor module
● 3-wire connection	BU type A0 with AUX terminals or potential distributor module
Digital outputs	
Type of digital output	Sink output (NPN)
Number of digital outputs	16
Current-sinking	Yes
Current-sourcing	No
Digital outputs, parameterizable	Yes
output type acc. to IEC 61131, type 0.5	Yes
Short-circuit protection	Yes; Electronic
● Response threshold, typ.	1 A
Limitation of inductive shutdown voltage to	Typ. 39 V
Controlling a digital input	Yes
Switching capacity of the outputs	
● with resistive load, max.	0.5 A
● with inductive load, max.	0.5 A; see additional description in the Equipment Manual
● on lamp load, max.	2.5 W
Load resistance range	
● lower limit	48 Ω
● upper limit	12 kΩ
Output current	
● for signal "1" rated value	0.5 A
● for signal "1" permissible range, max.	0.5 A
● for signal "0" residual current, max.	5 µA
Output delay with resistive load	
● "0" to "1", typ.	100 µs
● "1" to "0", typ.	300 µs
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	100 Hz
● with inductive load (acc. to IEC 60947-5-1, DC13), max.	0.1 Hz; higher frequencies are possible, see Equipment Manual "Maximum permitted switching frequency of inductive loads"
● on lamp load, max.	10 Hz
Total current of the outputs	
● Current per channel, max.	0.5 A
● Current per module, max.	8 A; see Equipment Manual "Derating curve"
Total current of the outputs (per module)	
horizontal installation	
— up to 40 °C, max.	8 A
— up to 50 °C, max.	6 A
— up to 60 °C, max.	4 A
vertical installation	
— up to 30 °C, max.	8 A
— up to 40 °C, max.	6 A
— up to 50 °C, max.	4 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes

Subject to change without notice
© Copyright Siemens

Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	No
● Short-circuit	No
● Group error	Yes
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	No
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● Between the channels and load voltage L+	No
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Suitable for safety-related tripping of standard modules	No
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	29.3 kg
— global warming potential, (during production) [CO2 eq]	3.98 kg
— global warming potential, (during operation) [CO2 eq]	25.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.245 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual
Absolute humidity	
● dew point, min.	-60 °C; suitable for dry room applications
Dimensions	
Width	15 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	30 g
Classifications	

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599

Subject to change without notice
© Copyright Siemens

ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration | EG-Konf. | UKCA | UL | RCM

General Product Approval	EMV	For use in hazardous locations

China RoHS | EG-Konf. | UKCA | KC | KC | UL

For use in hazardous locations

FM | CCC-Ex | IECEx | Miscellaneous | ATEX | Type Examination Certificate

For use in hazardous locations	Maritime application

CCC-Ex | ABS | BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai

Maritime application	Environment

RINA | CCS (China Classification Society) | KR (Korean Register of Shipping) | EPD

last modified: 6/22/2026

© Copyright Siemens