SIEMENS

Data sheet 3RW4900-0NC00



Communication module PROFINET for SIRIUS soft starter 3RW44 required product version 3RW44 >= *12*. implemented for starters 3RW44 from delivery date June 2013

product brand name	SIRIUS
product category	Communication modules
product designation	Communication module
design of the product	For 3RW44 soft starter integration in the PROFINET network, suitable for devices with firmware version E12 or higher
product type designation	3RW49
General technical data	
Substance Prohibitance (day/month/year)	11/13/2013
SVHC substance name	Lead monoxide (lead oxide) CAS-No. 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1 4,4'-isopropylidenediphenol (Bisphenol A, BPA) CAS-No. 80-05-7
Net Weight	0.195 kg
Installation/ mounting/ dimensions	
height	117.3 mm
width	36.6 mm
depth	111 mm
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe, for vertical contact from the front

Approvals Certificates

Environment	General Product Approval				EMV
Environmental Con-firmations	cULus	EAC	CE EG-Konf.	UKCA	KC

EMV	Test Certificates	Maritime application		other	
RCM	Special Test Certific-ate	DNV	PRS	Confirmation	产品合格 QC PASS


Industrial Communication

PROFINET


Subject to change without notice
© Copyright Siemens


Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW4900-0NC00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0NC00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW4900-0NC00&lang=en
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW4900-0NC00
Kennlinien
https://curves.simaris.siemens.com/curves/3RW4900-0NC00
Characteristic: Tripping characteristics, I²t, Let-through current
https://support.industry.siemens.com/cs/ww/en/ps/3RW4900-0NC00/char
Characteristic: Installation altitude
https://www.automation.siemens.com/bilddb/index.aspx?gridview=view2&objkey=G_NSB0_XX_01704&showdetail=true&view=Search
Simulation Tool for Soft Starters (STS)
https://support.industry.siemens.com/cs/ww/en/view/101494917



© Copyright Siemens





last modified: 4/2/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens