SIEMENS

Data sheet 6DL1138-6EC00-0EH1

Siemens EcoTech

SIMATIC ET 200SP HA, vibration protection 4xAI, 8xAQ, 4xDI, 6xDI/DQ suitable for terminal block H1, N0 color code CC00,



General information	
Product type designation	Vibration protection module 4 channels
HW functional status	FS04
Firmware version	V1.2
● FW update possible	Yes
Usable terminal block	type H1, N0, H0 (see system manual for details)
Color code for module-specific color-coded label	CC00
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 configurable/integrated from version	V5.6 with HSP 298 or higher
● PCS 7 configurable/integrated from version	V9.1 SP1
● SPPA-T3000 can be configured/integrated from version	V8.2 SP2
Operating mode	
● DI	Yes
● DQ	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	150 mA; without load
Current consumption, max.	2 A; At 24 V DC
from backplane bus 24 V DC, max.	21 mA
Encoder supply	
Number of outputs	6; max. depending on parameterization
Output voltage (DC)	24 V
Output voltage, min.	18.2 V
Short-circuit protection	Yes; per channel, electronic
24 V encoder supply	
● 24 V	Yes
● Short-circuit protection	Yes; per channel, electronic

Subject to change without notice
© Copyright Siemens

● Output current per channel, max.	0.5 A
● Output current per module, max.	2 A
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
● Address space per module, max.	162 byte; Quick inputs and outputs (without AI) and 4 vibration protection function chains: 88 bytes. Of which 71 bytes for inputs, 17 bytes for outputs. Quick inputs and outputs (without AI) and 8 vibration protection function chains: 154 bytes. Of which 137 bytes for inputs, 17 bytes for outputs. Quick inputs and outputs (with AI) and 4 vibration protection function chains 96 bytes. Of which 79 bytes for inputs, 17 bytes for outputs. Quick inputs and outputs (with AI) and 8 vibration protection function chains: 162 bytes. Of which 145 bytes for inputs, 17 bytes for outputs.
Hardware configuration	
Automatic encoding	
● Mechanical coding element	Yes; A, B coding; mounting position B8
Digital inputs	
Number of digital inputs	10; Of these, 6 combined DI/DQ
Digital inputs, parameterizable	Yes
Sourcing/sinking input	Yes; DI0 ... DI3 (param.); sinking DIDQ4 ... DIDQ9
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Pulse extension	Yes
● Length	2 s; off, 50 ms, 100 ms, 200 ms, 500 ms, 1 s, 2 s
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	0 ... 5 V
● for signal "1"	+11 to +30V
Input current	
● for signal "1", typ.	2.6 mA; 2.6 mA DI, 3.5 mA DIDQ
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms (in each case + delay of 30 to 500 µs, depending on line length)
Cable length	
● shielded, max.	1 000 m
Digital outputs	
Number of digital outputs	6; max. depending on parameterization
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
● Response threshold, typ.	0.95 A
Open-circuit detection	Yes
● Response threshold, typ.	45 mA
Overload protection	Yes
● Response threshold, typ.	950 mA
Limitation of inductive shutdown voltage to	L+ -(37 to 41V)
Controlling a digital input	Yes
Digital output functions, parameterizable	
● Freely usable digital output	Yes
Switching capacity of the outputs	
● with resistive load, max.	0.5 A
Load resistance range	
● lower limit	48 Ω
Output voltage	
● for signal "1", min.	18.1 V
Output current	
● for signal "1" rated value	0.5 A
Output delay with resistive load	
● "0" to "1", typ.	1 ms

© Copyright Siemens

● "1" to "0", typ.	100 µs
Switching frequency	
● with resistive load, max.	800 Hz
Total current of the outputs	
● Current per channel, max.	0.5 A
● Current per module, max.	2 A
Cable length	
● shielded, max.	1 000 m
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	30 V
permissible input current for current input (destruction limit), max.	50 mA; Protection available against destruction
Cycle time (all channels), min.	1.25 ms; For up to 128 samples per channel
Input ranges (rated values), voltages	
● 0 to +10 V	Yes
— Input resistance (0 to 10 V)	100 kΩ
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
Input ranges (rated values), currents	
● 0 to 20 mA	Yes; 0 mA or 4 mA to 20 mA
— Input resistance (0 to 20 mA)	70 Ω
● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	70 Ω
● 4 mA to 20 mA	Yes; and 0 to 20 mA
— Input resistance (4 mA to 20 mA)	70 Ω
Cable length	
● shielded, max.	600 m
Analog outputs	
Number of analog outputs	8; 4 AQ-I, 4 AQ-U
Voltage output, short-circuit protection	Yes; per channel, electronic to chassis
Voltage output, short-circuit current, max.	10 mA
Current output, no-load voltage, max.	24 V
Cycle time (all channels), min.	625 µs
Output ranges, voltage	
● -10 V to +10 V	Yes
Output ranges, current	
● 0 to 20 mA	Yes
● -20 mA to +20 mA	Yes; ±30 mA, ±50 mA
● 4 mA to 20 mA	Yes
Connection of actuators	
● for voltage output two-wire connection	Yes
Load impedance (in rated range of output)	
● with current outputs, max.	330 Ω; 150 ohms at ±50 mA
Analog value generation for the inputs	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	24 bit
Smoothing of measured values	
● Parameterizable	Yes
● Step: None	Yes
● Step: low	Yes
● Step: Medium	Yes
● Step: High	Yes
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
Encoder	

© Copyright Siemens

Connection of signal encoders	
● for voltage measurement	Yes
● for current measurement as 2-wire transducer	Yes
● for current measurement as 4-wire transducer	Yes
Connectable encoders	
● Single contact / changeover contact unconnected	Yes
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.05 %
Temperature error (relative to input range), (+/-)	0.0025 %/K
Crosstalk between the inputs, min.	60 dB
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.3 %
● Current, relative to input range, (+/-)	0.3 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes
Alarms	
● Diagnostic alarm	Yes
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire break	Yes; AI 4 ... 20 mA, AQ, DQ, DI 0 ... 3
● Short-circuit to ground	Yes; Encoder supply to M, channel by channel
● Short-circuit to L+	Yes; Analog inputs
● Group error	Yes
● Overflow/Underflow	Yes
Diagnostics indication LED	
● RUN LED	Yes; green LED
● MAINT LED	Yes; Yellow LED
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels and backplane bus	Yes
Permissible potential difference	
between different circuits	75 V DC/60 V AC between L+ and backplane bus
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C; Observe derating
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	3 500 m
Dimensions	
Width	22.5 mm
Height	115 mm
Depth	138 mm
Weights	
Weight, approx.	200 g

Classifications

	Version	Classification
eClass	16	27-23-01-90
eClass	14	27-23-01-90
eClass	12	27-23-01-90

Subject to change without notice
© Copyright Siemens

eClass	9.1	27-23-01-90
eClass	9	27-23-01-90
eClass	8	27-23-01-90
eClass	7.1	27-23-01-90
eClass	6	27-23-01-90
ETIM	10	EC000236
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236

Approvals / Certificates

General Product Approval

China RoHS

General Product Approval

Manufacturer Declaration

Declaration of Conformity

For use in hazardous locations

For use in hazardous locations

Miscellaneous

Environment

last modified: 2/11/2026

Subject to change without notice
© Copyright Siemens