SIEMENS

Data sheet for SINUMERIK BEDIENTAFELFRONT OP 019

Article No. : 6FC5303-0AF13-0AA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Screen	
Screen diagonal	19.0 in TFT color SXGA
Screen resolution	1,280 x 1,024

Rated data	
Input voltage	DC 5 V
	Via PCU or TCU 30.2
Power consumption	
Maximum	45.0 W
Standard	35.0 W

Mechanical data	
Net weight	11.0 kg (24.25 lb)
Width	483 mm (19.02 in)
Height	399.0 mm (15.71 in)
Depth	58 mm (2.30 in)
Installation depth	47.5 mm (1.87 in)
with TCU	81.0 mm (3.19 in)
with PCU 50	132.0 mm (5.20 in)
	Clearance + 10 mm (0.39 in)
Mounting surface	
Cutout width	450.0 mm (17.72 in)
Cutout height	380.0 mm (14.96 in)
Degree of protection	
Front side	IP65/IP66
Rear side	IP20 / UL open type

Ambient conditions	
Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Ambient temperature	
Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Storage	-20 ... 55 °C (-4 ... 131 °F)
Transport	-20 ... 55 °C (-4 ... 131 °F)
Relative humidity	
Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CE / cULus