SIEMENS

Data sheet 3VL5750-1EC46-0AA0

circuit breaker VL630N standard breaking capacity Icu=55kA, 415V AC 4-pole, line protection trip unit TM, LI In=500A, rated current IR=400...500A, overload protection, II=2500...5000A, short-circuit protection N protected without auxiliary release without auxiliary/alarm switch, spare part product only for replacement purposes

Weight	12.202 kg
Net Weight	12.202 kg

Approvals / Certificates

Environment		General Product Approval			
Environmental Confirmations	Environmental Confirmations	CCC	EAC	Confirmation	UKCA

Test Certificates	other			
Special Test Certificate	Miscellaneous	产品合格 QC PASS	Confirmation	Miscellaneous

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (catalogues, leaflets,...)
https://www.siemens.com/energy-automation
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL5750-1EC46-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3VL5750-1EC46-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5750-1EC46-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Kennlinien
https://curves.simaris.siemens.com/curves/3VL5750-1EC46-0AA0

last modified: 11/24/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens