SIEMENS

Data sheet 6XV1876-2A

product type designation	**IE FC TP standard cable GP 4x2, CAT7, sold by the meter**
product description	shielded TP installation cable (8-wire) with rigid cores, sold by the meter, unassembled
	IE FC TP Standard Cable GP 4x2; FastConnect Standard Cable GP 4x 2, TP installation CAT7 cable for connection to IE FC RJ45 plug 4x 2 and IE FC M12 plug PRO 4x2, AWG25, sold by the meter, package item max. 2000 m minimum order quantity 20 m



product brand name	SIMATIC NET
Technical Product Detail Page	https://i.siemens.com/1P6XV1876-2A
suitability for use	Standard cable with rigid cores for fast, permanent installation
cable designation	SF/FTP, 2YCY 4X2X0.45/1.15-100LI PIMF GN
electrical data	
attenuation factor per length	
● at 10 MHz / maximum	0.059 dB/m
● at 100 MHz / maximum	0.19 dB/m
● at 300 MHz / maximum	0.342 dB/m
● at 600 MHz / maximum	0.501 dB/m
impedance	
● at 1 MHz ... 100 MHz	100 Ω
near-end crosstalk per length	
● at 10 MHz	0.78 dB/m
● at 100 MHz	0.724 dB/m
● at 300 MHz	0.652 dB/m
● at 600 MHz	0.607 dB/m
loop resistance per length / maximum	290 mΩ/m
operating voltage	
● RMS value	100 V
● maximum	100 V
NVP value in percent	69 %
mechanical data	
number of electrical cores	8
design of the shield	SF/FTP, overlapped aluminum-clad foil, sheathed in a protective braided shield of tinned copper wires, central shielding wire of the line must be connected to the shield contact during plug assembly (see assembly video)
type of electrical connection / FastConnect	Yes
outer diameter	
● of inner conductor	0.45 mm
● of dielectric	3.8 mm
● of the wire insulation	1.15 mm
● of cable sheath	8 mm
symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
material	
● of the wire insulation	polyethylene (PE)
● of cable sheath	PVC

Subject to change without notice
© Copyright Siemens

color	
● of the insulation of data wires	white-blue/blue, white-orange/orange, white-green/green, white-brown/brown
● of cable sheath	green
bending radius	
● with single bend / minimum permissible	40 mm
● with multiple bends / minimum permissible	80 mm
tensile load / maximum	100 N
weight per length	69 kg/km
ambient conditions	
ambient temperature	
● during operation	-40 ... +70 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
● during installation	-30 ... +70 °C
fire behavior	flame resistant according to IEC 60332-1-2
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
● to mineral oil	oil resistant according to EN 50290-2-22 (VDE 0819), compound type TM55 (7x24h/90 °C)
● to grease	Conditional resistance
● to water	conditional resistance
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
● halogen-free	No
● PoE capability	Yes
● PoE+ capability	Yes
● PoE++ capability	Yes
● silicon-free	Yes
wire length / for Industrial Ethernet	
● with 100BaseTX	100 m
● with 1000BaseT	100 m
● for 10GBase T	70 m
● for 2.5GBaseT	100 m
● for 5GBaseT	100 m
test voltage	
● at AC / core-to-core	2000 V
● at AC / core shield	2000 V
standards, specifications, approvals	
UL/ETL listing / 300 V Rating	Yes
UL/ETL style / 600 V Rating	Yes
certificate of suitability	
● EAC approval	Yes
● CE marking	Yes
● RoHS conformity	Yes
product conformity	
● ANSI/TIA-EIA 568-B.2 Cat.5e	Yes
● IEC 61784-5-2-CP 2/2 (Ethernet/IP)	Yes
standard for structured cabling	Cat7
● resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Det Norske Veritas (DNV)	No
● Germanische Lloyd (GL)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No

Subject to change without notice
© Copyright Siemens

● Polski Rejestr Statkow (PRS)	No

further information / internet links

internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval			other	Environment
Manufacturer Declaration	CE EG-Konf.	CE EG-Konf.	Declaration of Conformity	Miscellaneous	Environmental Confirmations

Environment

Environmental Confirmations

last modified: 3/10/2026

Subject to change without notice
© Copyright Siemens