SIEMENS

Data sheet 3RK2200-0CG00-2AA2



AS-i SlimLine Compact module SC17.5 digital, A/B slave 4 DI, IP20 4 x input for 2-wire sensor spring-type terminals Overall width 17.5 mm

product designation	Slimline Compact I/O module for use in the control cabinet
design of the product	AS-i SC17.5, 4DI A/B, 2-wire
product type designation	3RK2
design of the device type	A/B slave
AS-Interface device profile	S-0.A.0
ID1 code	7; Factory setting, changeable
operating voltage according to AS-Interface specification	18 ... 31.6 V
product function suitable for AS-i Power24V	Yes
consumed current from profile conductors of the AS-Interface	
● at 30 V maximum	270 mA
● at 24 V with AS-i Power24V maximum	270 mA
type of address setting of the AS-i devices	via front addressing socket
Substance Prohibitance (day/month/year)	05/01/2012
SVHC substance name	Lead CAS-No. 7439-92-1 Lead monoxide (lead oxide) CAS-No. 1317-36-8 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1 Diboron trioxide CAS-No. 1303-86-2
Net Weight	0.094 kg
reference code	
● according to EN 61346-2	K
● according to DIN 40719 extended according to IEC 204-2 according to IEC 750	A
shock resistance	15 g / 11 ms (modules) or 10 g / 11 ms (modules with device connector)
Digital Inputs	
number of digital inputs	4
number of digital inputs safety-related	0
type of input characteristic	PNP Type 2
type of connection technology	2-wire technology
Sensor supply	
type of voltage supply for sensor supply	using AS-Interface
ampacity of the sensor supply for all inputs at ambient temperature 40 °C	200 mA
property of the sensor supply short-circuit and overload resistant	Yes
voltage drop at the sensor supply	
● from AS-interface	8.5 V
Digital Outputs	
number of digital outputs	0

Subject to change without notice
© Copyright Siemens

Analog inputs	
number of analog inputs	0
Analog outputs	
number of analog outputs	0
Device connector	
ampacity of the interface to the device connector	
● for AS-Interface	2 A
Installation/ mounting/ dimensions	
fastening method	screw and snap-on mounting
height	100 mm
width	17.5 mm
depth	120 mm
Ambient conditions	
ambient temperature	
● during operation	-25 ... +70 °C
● during storage	-40 ... +85 °C
Connections/ Terminals	
type of electrical connection of the inputs and outputs	spring-loaded terminal (push-in)
type of connectable conductor cross-sections	
● solid	1x (0.5 ... 1.5 mm²), 2x (0.5 ... 1.5 mm²)
● finely stranded with core end processing	1x (0,25 ... 1,0 mm²), 2x (0,25 ... 1,0 mm²)
● finely stranded without core end processing	1x (0.5 ... 1.5 mm²), 2x (0.5 ... 1.5 mm²)
● for AWG cables solid	1x (20 ... 16), 2x (20 ... 16)
● for AWG cables stranded	1x (20 ... 16), 2x (20 ... 16)

Approvals Certificates

Environment	General Product Approval				EMV
Environmental Confirmations	cULus	EAC	CE EG-Konf.	UKCA	RCM

Test Certificates	Maritime application			other	
Type Test Certificates/Test Report	ABS	DNV	LRS	Miscellaneous	Confirmation

other	Industrial Communication
产品合格 QC PASS	ASi

Further information

Siemens is working on the renewal of the current EAC certificates.
Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Siemens has decided to exit the Russian market (see here).
https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875

Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012


Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK2200-0CG00-2AA2


Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK2200-0CG00-2AA2

© Copyright Siemens

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3RK2200-0CG00-2AA2
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK2200-0CG00-2AA2&lang=en



Subject to change without notice
© Copyright Siemens



last modified: 4/4/2026

Subject to change without notice
© Copyright Siemens