SIEMENS

Data sheet 6AG1195-7KF00-2XA0



spare part SIPLUS S7-300 isolation module based on 6ES7195-7KF00-0XA0 with conformal coating, -25…+60 °C, isolation module between F and standard modules with redundant ET 200M connections, only use with isolating bus module

General information	
based on	6ES7195-7KF00-0XA0
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C; = Tmin
● max.	60 °C; = Tmax
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and	* The supplied plug covers must remain in place over the unused interfaces during operation!

Subject to change without notice
© Copyright Siemens

ANSI/ISA-71.04	

Accessories	
belongs to product	ET 200M

Weights	
Weight, approx.	10 g

Classifications

	Version	Classification
eClass	16	27-24-22-92
eClass	14	27-24-22-92
eClass	12	27-24-22-92
eClass	9.1	27-24-22-92
eClass	9	27-24-22-92
eClass	8	27-24-92-90
eClass	7.1	27-24-92-90
eClass	6	27-24-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

CE EG-Konf.	Manufacturer Declaration	UKCA	TUEV	UL	EAC

General Product Approval	EMV		For use in hazardous locations		
China RoHS	KC	RCM	IECEx IECEx	Ex ATEX	CCC-Ex

Functional Saftey	Test Certificates
TUEV	TUEV

last modified: 5/29/2024

Subject to change without notice
© Copyright Siemens