SIEMENS

Data sheet 3KC0426-2ME00-0AA0

SENTRON, 3KC transfer switching equipment, manually operated, MTSE, size: 1, 4-pole, Iu: 63 A, Ue AC: 415 V, Ie at AC-33 B at 415 V: 63 A, Ie at AC-23 A at 690 V: 63 A, screw and standard mounting rail installation 35 mm, front operating mechanism, centered, without handle, box terminal



Model	
product brand name	SENTRON
product designation	transfer switching equipment
design of the product	manually operated
display version for switch position indicator door-coupling rotary operating mechanism	I ON- O OFF- II ON
design of the actuating element	Without handle
design of handle	without
type of the driving mechanism	Front operating mechanism
type of the driving mechanism motor drive	No
General technical data	
number of poles	4
type of device	fixed mounting
size of switch disconnector	1
mechanical service life (operating cycles) for function sequence O-I-O typical	15 000
I2t value	
● with closed switch for combination switch + fuse at 500 V maximum	13 300 A²·s
● with closed switch at 690 V for combination switch + gG fuse maximum	13 700 A²·s
● of the fuse at 415 V maximum permissible	26 505 A²·s
● of the fuse at 500 V maximum permissible	26 505 A²·s
● of the gG fuse at 690 V maximum permissible	24 005 A²·s
● with closed switch for combination switch + fuse at 415 V maximum	13 300 A²·s
position of the switch operating mechanism	in center
overvoltage category	III
degree of pollution	3
insulation voltage	
● rated value	1 000 V
Protection class	
protection class IP	IP20
protection class IP	
● with closed switch with cover or cable lug cover	IP20
● on the front	IP20
Dissipation	
power loss [W]	
● with conventional rated thermal current per device	8 W
Main circuit	

Subject to change without notice
© Copyright Siemens

operating power	
● at AC-23 A at 400 V at 50/60 Hz rated value	30 kW
● at AC-23 A at 500 V rated value	37 kW
operational current rated value	63 A
Auxiliary circuit	
number of connected NC contacts for auxiliary contacts	0
number of connected NO contacts for auxiliary contacts	0
number of connected CO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	8
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
suitability for use main switch	Yes
suitability for use switch disconnector	Yes
suitability for use EMERGENCY OFF switch	Yes
suitability for use maintenance/repair switch	Yes
product feature interlock	No
product extension auxiliary switch	Yes
product extension optional motor drive	No
product extension optional voltage trigger	No
Short circuit	
short-circuit current making capacity (Icm) for switch disconnector	
● at 415 V AC without fuse link according to IEC 60947-6-1 rated value minimum	7.7 kA
● at 690 V AC without fuse link according to IEC 60947-3 rated value minimum	7 kA
conditional short-circuit current with line-side fuse protection	
● at 415 V by gG fuse according to IEC 60947-6-1 rated value	100 kA
● at 415 V by gG fuse rated value	100 kA
● at 500 V by gG fuse according to IEC 60947-3 rated value	100 kA
● at 690 V by gG fuse according to IEC 60947-3 rated value	100 kA
Connections	
type of connectable conductor cross-sections with flexible busbar	2x (0.8x9 mm²)
type of connectable conductor cross-sections	
● for copper busbar	1x (2x9 mm²)
type of connectable conductor cross-sections for copper conductor	
● solid	1x (1 ... 16 mm²)
● finely stranded with core end processing	1x (1 ... 35 mm²)
● stranded	1x(6...35 mm²)
type of electrical connection	
● for main current circuit	box terminal
Mechanical Design	
height	119 mm
width	237.6 mm
depth	84.5 mm
fastening method	Screw fixing and standard rail mounting 35 mm
fastening method	
● 4-hole front mounting	No
● front mounting with central attachment	No
● rail mounting	Yes
mounting position	any
Net Weight	1.909 kg
Environmental conditions	
ambient temperature during operation	
● minimum	-25 °C

Subject to change without notice
© Copyright Siemens

• maximum	70 °C
ambient temperature during storage	
• minimum	-50 °C
• maximum	80 °C

Approvals Certificates

Environment		General Product Approval		Miscellaneous	
Environmental Con-firmations	Environmental Con-firmations	CCC	VDE		EAC


General Product Approval		Test Certificates	Maritime application	
Confirmation	CE EG-Konf. UKCA	Type Test Certific-ates/Test Report	DNV	Lloyd's Register LRS


other	
Confirmation	产品合格 QC PASS


Further information


Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KC0426-2ME00-0AA0
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3KC0426-2ME00-0AA0
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KC0426-2ME00-0AA0
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications
Kennlinien
https://curves.simaris.siemens.com/curves/3KC0426-2ME00-0AA0


Subject to change without notice
© Copyright Siemens











Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens