SIEMENS

Data sheet 6GK5552-0AA00-2AR2

SCALANCE XR552-12M; managed IE switch; 19" rack; 4x 1000/10000 Mbit/s SFP+; 12x 100/1000 Mbit/s 4-port media modules, electrical, electrical PoE or optical; LED diagnostics; error signaling contact; Select/set pushbutton, PROFINET IO device, network management, integrated redundancy manager; office features (RSTP, VLAN, IGMP, ...); C-plug in scope of delivery Layer 3 prepared; ports in the front.



product type designation	
product brand name	SCALANCE
product type designation	XR552-12M
Technical Product Detail Page	https://i.siemens.com/1P6GK5552-0AA00-2AR2
transfer rate	
transfer rate	10, 100, 1000 Mbit/s
transfer rate	10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	RJ45
● for Power-over-Ethernet / for network components or terminal equipment	12
number of electrical connections	
● for SFP+	4
interfaces / for communication / plug-in	
number of 100 Mbit/s ST(BFOC) ports	
● for multimode	48
● for single mode (LD)	48
number of 1000 Mbit/s SC ports	
● for multimode	48
● for single mode (LD)	48
number of electrical connections	
● for SFP	4
● for SFP+	4
interfaces / other	
number of electrical connections	
● for operator console	1
● for signaling contact	1
● for media module	12
● for power supply	1
type of electrical connection	
● for operator console	RJ11
● for management purposes	RJ45
● for signaling contact	2-pole terminal block
● for power supply	4-pole terminal block
product feature / hot-swappable interface modules	Yes
operating voltage / of the signaling contacts	
● at DC / rated value	24 V
operational current / of the signaling contacts	

Subject to change without notice
© Copyright Siemens

● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
type of voltage supply / redundant power supply unit	No
supplied active power / of PSE / with PoE	
● per port / maximum	30 W
● total / maximum	180 W
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	34.08 W
● supply voltage / 1 / voltage range	19.2 ... 28.8
● consumed current / 1 / maximum	12.5 A
● type of electrical connection / 1 / for power supply	4-pole terminal block
● product component / 1 / fusing at power supply input	Yes
● fuse protection type / 1 / at input for supply voltage	F 15 A / 125 V
ambient conditions	
ambient temperature	
● during operation	0 ... 60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
● note	Operation with integral fan, replaceable
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	19-inch rack
number of modular height units / relating to 19-inch cabinet	3
width	449 mm
height	130.8 mm
depth	305 mm
net weight	10 kg
fastening method	
● 19-inch installation	Yes
● 35 mm DIN-rail mounting	No
● wall mounting	No
● S7-300 rail mounting	No
● S7-1500 rail mounting	No
type of cable outlet	Cable outlet at front
product features, product functions, product components / general	
cascading in cases of star topology	any (depending only on signal propagation time)
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● RMON	Yes
● port mirroring	Yes
● multiport mirroring	Yes
● CoS	Yes
● PROFINET IO diagnosis	Yes
● switch-managed	Yes
PROFINET conformity class	B
telegram length / for Ethernet / maximum	9216 byte
protocol / is supported	
● Telnet	Yes
● HTTP	Yes
● HTTPS	Yes

Subject to change without notice
© Copyright Siemens

● TFTP	Yes
● FTP	Yes
● BOOTP	Yes
● GMRP	Yes
● DCP	Yes
● LLDP	Yes
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v3	Yes
● IGMP (snooping/querier)	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
● SysLog	Yes
product functions / VLAN	
product function	
● VLAN - port based	Yes
● VLAN - protocol-based	Yes
● VLAN - IP-based	Yes
● VLAN dynamic	Yes
number of VLANs / maximum	255
number of VLANs - dynamic / maximum	255
product functions / DHCP	
product function	
● DHCP client	Yes
● DHCP Option 82	Yes
● DHCP Option 66	Yes
● DHCP Option 67	Yes
product functions / routing	
service / routing / note	IP routing in combination with KEY-PLUG XR-500
product function	
● static IP routing	Yes
● static IP routing IPv6	Yes
● dynamic IP routing	Yes
● dynamic IP routing IPv6	Yes
protocol / is supported	
● RIPv2	Yes
● RIPnG for IPv6	Yes
● OSPFv2	Yes
● OSPFv3 for IPv6	Yes
● VRRP	Yes
● VRRP for IPv6	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● Media Redundancy Protocol Interconnection (MRP-I)	Yes; LC mode
● ring redundancy	Yes
● high speed redundancy protocol (HRP) with redundancy manager	Yes
● high speed redundancy protocol (HRP) with standby redundancy	Yes

Subject to change without notice
© Copyright Siemens

● redundancy procedure STP	Yes
● redundancy procedure RSTP	Yes
● redundancy procedure RSTP+	Yes
● redundancy procedure MSTP	Yes
● Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
● passive listening	Yes
protocol / is supported	
● LACP	Yes
product functions / security	
product function	
● IEEE 802.1x (radius)	Yes
● broadcast/multicast/unicast limiter	Yes
● broadcast blocking	Yes
protocol / is supported	
● SSH	Yes
product functions / time	
product function	
● SICLOCK support	Yes
protocol / is supported	
● NTP	Yes
● SNTP	Yes
type of time synchronization	IEEE 1588
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● KC approval	Yes
● Regulatory Compliance Mark (RCM)	Yes
standard	
● for EMC interference emission	EN 61000-6-4 (Class A)
● for immunity to EMC	EN 61000-6-2
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1-03
standards, specifications, approvals / hazardous environments	
certificate of suitability	
● ATEX	Yes
● UKEX	Yes
● IECEx	Yes
● ULhazloc approval	Yes
● CCC / for hazardous zone according to GB standard	Yes
● FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
● RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	1077.71 kg
● during manufacturing	132 kg
● during operation	945.12 kg
● after end of life	0.59 kg
product functions / general	
warranty period	5 a
further information / internet links	
internet link	

© Copyright Siemens

● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

Environmental Product Declaration

● global warming potential [CO2 eq] / during manufacturing	132 kg
● global warming potential [CO2 eq] / during operation	945.12 kg
● global warming potential [CO2 eq] / after end of life	0.59 kg
● global warming potential [CO2 eq] / total	1077.71 kg

Environment | **General Product Approval**

EPD | CE EG-Konf. | Declaration of Conformity | CCC | EAC | China RoHS

General Product Approval | **EMV**

Manufacturer Declaration | RCM | CE EG-Konf. | China RoHS | UKCA | KC

For use in hazardous locations | **Industrial Communication**

IECEx | ATEX | FM | CCC-Ex | PROFINET

last modified: 8/28/2026

Subject to change without notice
© Copyright Siemens