SIEMENS

Data sheet 6AV6646-1BC15-0AA0



spare part SIMATIC ITC1500 V3 Pro, industrial thin client, 15" widescreen TFT display, capacitive touch sensor supported protocols: RDP, VNC, SmartServer HTML5 and others, standard design, prepared for support arm without expansion elements

General information	
Product type designation	ITC1500 V3 PRO
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	15.6 in; 15"
Display width	344.2 mm
Display height	193.5 mm
Number of colors	16 777 216
Resolution (pixels)	
● Image resolution	1 366 x 768
● Horizontal image resolution	1 366 pixel
● Vertical image resolution	768 pixel
General features	
● non-reflective and tempered mineral glass screen	Yes
● Detachable from computer unit	100 m
Backlighting	
● Type of backlighting	LED, dimmable
● MTBF backlighting (at 25 °C)	50 000 h; At 25°C
● Backlight dimmable	Yes
Control elements	
Control elements	multi-touch screen
Touch operation	
● Design as touch screen	Yes
● Design as multi-touch screen	Yes; Projective-capacitive
● Monitor keyboard	Yes
Installation type/mounting	
Design	Support arm mounting
Front mounting	No
Support arm mounting	Yes; Suitable for support arm without extension components
Stand mounting	No
Built-in unit	No
maximum permitted forward tilt angle from vertical	35°
maximum permitted backward tilt angle from vertical	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	

Subject to change without notice
© Copyright Siemens

Current consumption (rated value)	1.4 A
Starting current inrush I²t	0.5 A²·s
Power	
Active power input, typ.	34 W
Power loss	
Power loss, typ.	34 W
Interfaces	
Number of industrial Ethernet interfaces	2; 2 ports (switch)
Number of USB interfaces	4; on rear
USB on the rear	Yes; 2x onboard
Connection for keyboard/mouse	USB
Industrial Ethernet	
● Transmission rate, max.	1 000 Mbit/s
Protocols	
Protocols (Ethernet)	
● TCP/IP	Yes
● DHCP	Yes
● SNMP	Yes
● DCP	Yes
● LLDP	Yes
WEB characteristics	
● HTTP	Yes
● HTTPS	Yes
● HTML	Yes; HTML5
● XML	Yes
● CSS	Yes
● Active X	No
● JavaScript	Yes
● Java VM	No
Protocols (terminal link)	
● Sm@rtServer	Yes
● RDP	Yes
● VNC viewer	Yes
● Citrix	Yes
● SINUMERIK	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP65
NEMA (front)	
● Enclosure Type 4 at the front	Yes
● Enclosure Type 4x at the front	Yes
● Enclosure Type 12 at the front	Yes
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Use in hazardous areas	
● ATEX Zone 2	No
● ATEX Zone 22	No
● IECEx Zone 2	No
● IECEx Zone 22	No
● cULus Class I Zone 2, Division 2	No
● FM Class I Division 2	No
Marine approval	
● Germanischer Lloyd (GL)	No
● American Bureau of Shipping (ABS)	No

© Copyright Siemens

● Bureau Veritas (BV)	No
● Det Norske Veritas (DNV)	No
● Korean Register of Shipping (KRS)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (Class NK)	No
● Polski Rejestr Statkow (PRS)	No
● Chinese Classification Society (CCS)	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	45 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Relative humidity	
● Operation, max.	90 %; no condensation
Vibrations	
● Vibration load in operation	10 m/s²
● Vibration load during transport/storage	10 m/s²
Shock testing	
● Shock load during operation	150 m/s²
● shock acceleration during storage/transport	150 m/s²
Software	
Web browser	Yes; HTML5, CSS
PDF reader	Yes
Configuration	
Configuration	
● Local	Yes
● Remote	Yes; Via web page
Languages	
Online languages	
● Number of online/runtime languages	2; german / english
Peripherals/Options	
USB memory	Yes; USB storage medium can be connected
Mechanics/material	
Enclosure material (front)	
● Aluminum	Yes
Dimensions	
Width of the housing front	396 mm
Height of housing front	256 mm; Without basic adapter
Weights	
Weight (without packaging)	6.3 kg
Classifications	

	Version	Classification
eClass	16	19-20-01-03
eClass	14	19-20-01-03
eClass	12	19-20-01-03
eClass	9.1	19-20-01-03
eClass	9	19-20-01-03
eClass	8	27-24-23-01
eClass	7.1	27-24-23-01
eClass	6	27-24-23-01
ETIM	10	EC001414
ETIM	9	EC001414
ETIM	8	EC001414
ETIM	7	EC001414

Subject to change without notice
© Copyright Siemens

	IDEA	4	6607
	UNSPSC	15	43-21-15-06

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration

General Product Approval

China RoHS | Manufacturer Declaration

EMV

last modified: 9/11/2026

Subject to change without notice
© Copyright Siemens