SIEMENS

Data sheet 6ES7416-5HS06-0AB0



SIMATIC S7-400H, CPU 416-5H, central processing unit for S7-400H and S7-400F/FH, 5 interfaces: 1x MPI/DP, 1x DP, 1x PN and 2 for sync modules, 16 MB memory (10 MB data/6 MB program)

General information	
Product type designation	CPU 416-5H PN/DP
HW functional status	1
Firmware version	V6.0
Product function	
● Isochronous mode	No
Engineering with	
● Programming package	As of STEP 7 V5.5 SP2 with HF1
CiR - Configuration in RUN	
CiR synchronization time, basic load	100 ms
CiR synchronization time, time per I/O byte	0 µs
Supply voltage	
Rated value (DC)	Power supply via system power supply
Input current	
from backplane bus 5 V DC, typ.	1.6 A
from backplane bus 5 V DC, max.	1.9 A
from backplane bus 24 V DC, max.	150 mA; 150 mA per DP interface
from interface 5 V DC, max.	90 mA; At each DP interface
Power loss	
Power loss, typ.	7.5 W
Storage	
Type of memory	RAM
Work memory	
● integrated	16 Mbyte
● integrated (for program)	6 Mbyte
● integrated (for data)	10 Mbyte
● expandable	No
Load memory	
● expandable FEPROM	Yes; with Memory Card (FLASH)
● expandable FEPROM, max.	64 Mbyte
● integrated RAM, max.	1 Mbyte
● expandable RAM	Yes
● expandable RAM, max.	64 Mbyte
Backup	
● present	Yes
● with battery	Yes; all data
● without battery	No
Battery	
Backup battery	

Subject to change without notice
© Copyright Siemens

● Backup current, typ.	180 µA; Valid up to 40°C
● Backup current, max.	1 000 µA
● Backup time, max.	Dealt with in the module data manual with the secondary conditions and the factors of influence
● Feeding of external backup voltage to CPU	5 V DC to 15 V DC
CPU processing times	
for bit operations, typ.	12.5 ns
for word operations, typ.	12.5 ns
for fixed point arithmetic, typ.	12.5 ns
for floating point arithmetic, typ.	25 ns
CPU-blocks	
DB	
● Number, max.	16 000; Number range: 1 to 16000
● Size, max.	64 kbyte
FB	
● Number, max.	8 000; Number range: 0 to 7999
● Size, max.	64 kbyte
FC	
● Number, max.	8 000; Number range: 0 to 7999
● Size, max.	64 kbyte
OB	
● Number, max.	see instruction list
● Size, max.	64 kbyte
● Number of free cycle OBs	1; OB 1
● Number of time alarm OBs	8; OB 10-17
● Number of delay alarm OBs	4; OB 20-23
● Number of cyclic interrupt OBs	9; OB 30-38
● Number of process alarm OBs	8; OB 40-47
● Number of DPV1 alarm OBs	3; OB 55-57
● Number of startup OBs	2; OB 100, 102
● Number of asynchronous error OBs	9; OB 80-88
● Number of synchronous error OBs	2; OB 121, 122
Nesting depth	
● per priority class	24
● additional within an error OB	2
Counters, timers and their retentivity	
S7 counter	
● Number	2 048
Retentivity	
— adjustable	Yes
— preset	Z 0 to Z 7
Counting range	
— lower limit	0
— upper limit	999
IEC counter	
● present	Yes
● Type	SFB
● Number	Unlimited (limited only by RAM capacity)
S7 timer	
● Number	2 048
Retentivity	
— adjustable	Yes
— preset	No times retentive
Time range	
— lower limit	10 ms
— upper limit	9 990 s
IEC timer	
● present	Yes
● Type	SFB

Subject to change without notice
© Copyright Siemens

● Number	Unlimited (limited only by RAM capacity)
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	Total working and load memory (with backup battery)
Flag	
● Size, max.	16 384 byte
● Retentivity available	Yes
● Retentivity preset	MB 0 to MB 15
● Number of clock memories	8; in 1 memory byte
Local data	
● adjustable, max.	64 kbyte
● preset	32 kbyte
Address area	
I/O address area	
● Inputs	16 kbyte
● Outputs	16 kbyte
Process image	
● Inputs, adjustable	16 kbyte
● Outputs, adjustable	16 kbyte
● Inputs, default	1 024 byte
● Outputs, default	1 024 byte
● consistent data, max.	244 byte
● Access to consistent data in process image	Yes
Subprocess images	
● Number of subprocess images, max.	15
Digital channels	
● Inputs	131 072
— of which central	131 072
● Outputs	131 072
— of which central	131 072
Analog channels	
● Inputs	8 192
— of which central	8 192
● Outputs	8 192
— of which central	8 192
Hardware configuration	
Number of expansion units, max.	21
connectable OPs	95
Multicomputing	No
Interface modules	
● Number of connectable IMs (total), max.	6
● Number of connectable IM 460s, max.	6
● Number of connectable IM 463s, max.	4; Single mode only
Number of DP masters	
● integrated	2
● via CP	10; CP 443-5 Extended
● Mixed mode IM + CP permitted	No
● via interface module	0
Number of IO Controllers	
● Integrated	1
● Via CP	0
Number of operable FMs and CPs (recommended)	
● FM	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
● CP, PtP	See manual Automation System S7-400H fault-tolerant systems. Limited by number of slots and number of connections
● PROFIBUS and Ethernet CPs	14; Of which max. 10 CP as DP master
Slots	
● required slots	2
Time of day	

© Copyright Siemens

Clock	
● Hardware clock (real-time)	Yes
● retentive and synchronizable	Yes
● Resolution	1 ms
● Deviation per day (buffered), max.	1.7 s; Power off
● Deviation per day (unbuffered), max.	8.6 s; Power on
Operating hours counter	
● Number	16
● Number/Number range	0 to 15
● Range of values	SFCs 2, 3 and 4: 0 to 32767 hours SFC 101: 0 to 2^31 - 1 hours
● Granularity	1 h
● retentive	Yes
Clock synchronization	
● supported	Yes
● to MPI, master	Yes
● on MPI, device	Yes
● to DP, master	Yes
● on DP, device	Yes
● in AS, master	Yes
● in AS, device	Yes
● on Ethernet via NTP	Yes; As client
Time difference in system when synchronizing via	
● Ethernet, max.	10 ms; Via NTP
● MPI, max.	200 ms
Interfaces	
Number of RS 485 interfaces	2
Number of other interfaces	2; Fiber-optic interface
Optical interface	No
1. Interface	
Interface type	MPI/PROFIBUS DP
Isolated	Yes
Interface types	
● RS 485	Yes
● Output current of the interface, max.	150 mA
Protocols	
● MPI	Yes
● PROFIBUS DP master	Yes
● PROFIBUS DP device	No
MPI	
● Number of connections	44; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
● Transmission rate, max.	12 Mbit/s
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
PROFIBUS DP master	
● Number of connections, max.	32; If a diagnostics repeater is used on the line, the number of connection resources on the line is reduced by 1
● Transmission rate, max.	12 Mbit/s
● max. number of DP devices	32
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No

© Copyright Siemens

— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	No
— Isochronous mode	No
— SYNC/FREEZE	No
— activation/deactivation of DP devices	No
— Direct data exchange (slave-to-slave communication)	No
— DPV1	Yes
Address area	
— Inputs, max.	2 kbyte
— Outputs, max.	2 kbyte
User data per DP device	
— user data per DP device, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
PROFIBUS DP device	
● Number of connections	No configuration of CPU as DP slave
2. Interface	
Interface type	PROFINET
Isolated	Yes
automatic detection of transmission rate	Yes; Autosensing
Autonegotiation	Yes
Autocrossing	Yes
Change of IP address at runtime, supported	No
Interface types	
● RJ 45 (Ethernet)	Yes
● Number of ports	2
● integrated switch	Yes
Protocols	
● PROFINET IO Controller	Yes
● PROFINET IO Device	No
● PROFINET CBA	No
● PROFIBUS DP master	No
● PROFIBUS DP device	No
● Open IE communication	Yes
● Web server	No
● Point-to-point connection	No
● Media redundancy	Yes
PROFINET IO Controller	
● Transmission rate, max.	100 Mbit/s
Services	
— PG/OP communication	Yes
— S7 communication	Yes
— Isochronous mode	No
— Shared device	Yes; Single mode only
— Prioritized startup	No
— Number of connectable IO Devices, max.	256; In redundant mode via both interfaces
— Number of connectable IO Devices for RT, max.	256
— of which in line, max.	256
— Activation/deactivation of IO Devices	No
— IO Devices changing during operation (partner ports), supported	No
— Device replacement without swap medium	Yes
— Send cycles	250 µs, 500 µs, 1 ms, 2 ms, 4 ms

© Copyright Siemens

— Updating time	250 µs to 512 ms, minimum value depends on the number of configured user data and the configured single or redundant mode
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
— User data consistency, max.	1 024 byte
Open IE communication	
● Number of connections, max.	94
● Local port numbers used at the system end	0, 20, 21, 25, 102, 135, 161, 34962, 34963, 34964, 65532, 65533, 65534, 65535
● Keep-alive function, supported	Yes
3. Interface	
Interface type	PROFIBUS DP
Interface types	
● RS 485	Yes
● Output current of the interface, max.	150 mA
Protocols	
● PROFIBUS DP master	Yes
● PROFIBUS DP device	No
PROFIBUS DP master	
● Number of connections, max.	32
● Transmission rate, max.	12 Mbit/s
● max. number of DP devices	125
Services	
— PG/OP communication	Yes
— Routing	Yes
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes
— S7 communication, as client	Yes
— S7 communication, as server	Yes
— Equidistance	No
— Isochronous mode	No
— SYNC/FREEZE	No
— activation/deactivation of DP devices	No
— Direct data exchange (slave-to-slave communication)	No
— DPV0	Yes
— DPV1	Yes
Address area	
— Inputs, max.	8 kbyte
— Outputs, max.	8 kbyte
User data per DP device	
— user data per DP device, max.	244 byte
— Inputs, max.	244 byte
— Outputs, max.	244 byte
— Slots, max.	244
— per slot, max.	128 byte
4. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0
5. Interface	
Interface type	Pluggable synchronization submodule (FO)
Plug-in interface modules	Synchronization modules 6ES7960-1AA06-0XA0 or 6ES7960-1AB06-0XA0
Protocols	
Redundancy mode	
Media redundancy	
— Switchover time on line break, typ.	200 ms
— Number of stations in the ring, max.	50
SIMATIC communication	

© Copyright Siemens

● S7 routing	Yes
Open IE communication	
● TCP/IP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	94
— Data length, max.	32 kbyte
— several passive connections per port, supported	Yes
● ISO-on-TCP (RFC1006)	Yes; Via integrated PROFINET interface or CP 443-1 and loadable FBs
— Number of connections, max.	94
— Data length, max.	32 kbyte; 1 452 bytes via CP 443-1 Adv.
● UDP	Yes; via integrated PROFINET interface and loadable FBs
— Number of connections, max.	94
— Data length, max.	1 472 byte
Web server	
● supported	No
Isochronous mode	
Equidistance	No
Communication functions	
PG/OP communication	Yes
● Number of connectable OPs with message processing	95; When using Alarm_S/SQ and Alarm_D/DQ
● Number of connectable OPs without message processing	95
Data record routing	Yes
Global data communication	
● supported	No
S7 basic communication	
● supported	No
S7 communication	
● supported	Yes
● as server	Yes
● as client	Yes
● User data per job, max.	64 kbyte
● User data per job (of which consistent), max.	462 byte; 1 variable
S5 compatible communication	
● supported	Yes; (via CP max. 10 and FC AG_SEND and FC AG_RECV)
● User data per job, max.	8 kbyte
● User data per job (of which consistent), max.	240 byte
● Number of simultaneous AG-SEND/AG-RECV orders per CPU, max.	64/64
Standard communication (FMS)	
● supported	Yes; Via CP and loadable FB
Number of connections	
● overall	96
● usable for PG communication	
— reserved for PG communication	1
— adjustable for PG communication, max.	0
● usable for OP communication	
— reserved for OP communication	1
— adjustable for OP communication, max.	0
● usable for S7 basic communication	
— reserved for S7 basic communication	0
— adjustable for S7 basic communication, max.	0
● usable for S7 communication	
— reserved for S7 communication	0
— adjustable for S7 communication, max.	0
● usable for routing	
— reserved for routing	0
— adjustable for routing, max.	0
S7 message functions	
Number of login stations for message functions, max.	95; Max. 95 with Alarm_S/SQ and Alarm_D/DQ (OPs); max. 16 with Alarm, Alarm_8, Alarm_8P, Notify and Notify_8 (e.g. WinCC)

© Copyright Siemens

Symbol-related messages	No
SCAN procedure	No
Program alarms	Yes
Process diagnostic messages	Yes
simultaneously active Alarm_S blocks, max.	1 000; Simultaneously active alarm_S/SQ blocks or alarm_D/DQ blocks
Alarm 8-blocks	Yes
● Number of instances for alarm 8 and S7 communication blocks, max.	10 000
● preset, max.	1 200
Process control messages	Yes
Number of archives that can log on simultaneously (SFB 37 AR_SEND)	64
Test commissioning functions	
Status block	Yes
Single step	Yes
Number of breakpoints	16
Status/control	
● Status/control variable	Yes; Up to 16 variable tables
● Variables	Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters
● Number of variables, max.	70
Forcing	
● Forcing	Yes
● Forcing, variables	Inputs/outputs, bit memories, distributed I/Os
● Number of variables, max.	512
Diagnostic buffer	
● present	Yes
● Number of entries, max.	3 200
— can be set	Yes
— preset	120
Service data	
● Can be read out	Yes
EMC	
Emission of radio interference acc. to EN 55 011	
● Limit class A, for use in industrial areas	Yes
● Limit class B, for use in residential areas	No
Configuration	
Configuration software	
● STEP 7	Yes
Programming	
● Command set	see instruction list
● Nesting levels	7
● Access to consistent data in process image	Yes
● System functions (SFC)	see instruction list
● System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Number of simultaneously active SFCs	
— RD_REC	8
— WR_REC	8
— WR_PARM	8
— PARM_MOD	1
— WR_DPARM	2
— DPNRM_DG	8

© Copyright Siemens

— RDSYSST	8
— DP_TOPOL	1
Number of simultaneously active SFBs	
— RDREC	8
— WRREC	8
Know-how protection	
● User program protection/password protection	Yes
● Block encryption	Yes; With S7 block Privacy
Dimensions	
Width	50 mm
Height	290 mm
Depth	219 mm
Weights	
Weight, approx.	995 g

Classifications

	Version	Classification
eClass	16	27-24-22-07
eClass	14	27-24-22-07
eClass	12	27-24-22-07
eClass	9.1	27-24-22-07
eClass	9	27-24-22-07
eClass	8	27-24-22-07
eClass	7.1	27-24-22-07
eClass	6	27-24-22-07
ETIM	10	EC000236
ETIM	9	EC000236
ETIM	8	EC000236
ETIM	7	EC000236
IDEA	4	3565
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | Miscellaneous

General Product Approval | **For use in hazardous locations**

China RoHS | Miscellaneous | Manufacturer Declaration

For use in hazardous locations | **Functional Saftey**

FM | Type Examination Certificate | TUEV

Functional Saftey | **Maritime application**

© Copyright Siemens

Type Examination Certificate

ABS

BUREAU VERITAS

DNV

LRS

NK / Nippon Kaiji Kyokai

Maritime application	Environment	Industrial Communication

RINA

CCS (China Classification Society)

EPD

PROFIsafe

last modified: 9/11/2026

Subject to change without notice
© Copyright Siemens