SIEMENS

Data sheet 6DR5215-0PN31-0AA0

	SIPART PS2 Smart, electropneumatic positioner, 4...20mA (3/4-wire), HART, Ex/nEx, single-acting, aluminum enclosure, flameproof (Ex d), for pneumatic linear and part-turn actuators. Standard Type of protection (Ex): Flameproof enclosure (Ex d), Intrinsic safety (Ex i), Dust ignition protection by enclosure (Ex t). Output isolator SITRANS I200 separately orderable (7NG4131-1AA00). Connection thread el.: 1/2" NPT / pneu.: 1/4" NPT Mechanic Limit Switches (MLS), 2 mechanical limit switches and 1 digital output Analog Output Module (AOM), analog position feedback 4 ... 20 mA. Isolating power supply SITRANS I100 separately orderable (7NG4124-1AA00). . Brief instructions English / German / Chinese. Standard / Fail-Safe - Depressurizing the actuator in case of failure of electrical auxiliary power (single acting only). Without Manometer block / Booster.

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens