SIEMENS

Data sheet 6ES7132-4FB01-0AB0



Figure similar

*** Spare part *** SIMATIC DP, 5 electronic modules for ET 200S, 2 DO 24...230 V AC 15 mm width, 5 units per packing unit

Supply voltage	
Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L1	
● permissible range, lower limit (AC)	24 V; From power module
● permissible range, upper limit (AC)	230 V
● permissible frequency range, lower limit	47 Hz
● permissible frequency range, upper limit	63 Hz
Input current	
from load voltage L1 (without load), max.	15 mA; Per channel
from backplane bus 3.3 V DC, max.	18 mA
Address area	
Address space per module	
● Address space per module, max.	1 byte
● with packing	2 bit
Digital outputs	
Type of digital output	Triac
Number of digital outputs	2
Short-circuit protection	Yes
Limitation of inductive shutdown voltage to	-55 to -60 V
Controlling a digital input	Yes; possible
Switching capacity of the outputs	
● on lamp load, max.	100 W
Output voltage	
● for signal "1", min.	L+ (-1.5 V)
Output current	
● for signal "1" rated value	2 A
● for signal "1" permissible range, min.	0.1 mA
● for signal "1" permissible range, max.	2.2 A
● for signal "0" residual current, max.	3 mA
Output delay with resistive load	
● "0" to "1", max.	15 ms
● "1" to "0", max.	15 ms
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Yes; per module
Switching frequency	
● with resistive load, max.	10 Hz
● with inductive load, max.	0.5 Hz

Subject to change without notice
© Copyright Siemens

● on lamp load, max.	1 Hz
Total current of the outputs	
● Current per module, max.	2 A; note derating data in the manual
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
● Status indicator digital output (green)	Yes
Potential separation	
Potential separation digital outputs	
● between the channels	No
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	2 500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weights	
Weight, approx.	37 g

Classifications

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599
ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

Manufacturer Declaration

General Product Approval				EMV	For use in hazardous locations
	China RoHS				FM

For use in hazardous locations	Maritime application

Subject to change without notice
© Copyright Siemens

UL ABS BUREAU VERITAS DNV LRS

NK / Nippon Kaiji Kyokai

Maritime application

PRS RINA

CCS (China Classification Society) KR (Korean Register of Shipping)

last modified: 8/22/2025

Subject to change without notice
© Copyright Siemens