SIEMENS

Data sheet 6EP3322-6SB10-0AY0



LOGO!Power/1AC/15VDC/4A

LOGO!POWER 15 V / 4 A stabilized power supply input: 100-240 V AC output: 15 V DC / 4 A

General information	
Technical Product Detail Page	https://i.siemens.com/1P6EP3322-6SB10-0AY0
product brand name	LOGO!Power
product type designation	LOGO!Power
product designation	Power supply LOGO!Power
type of current supply	15 V/4 A
input	
type of the power supply network	1-phase AC or DC
phase number	1
voltage curve at input	AC/DC
supply voltage at AC	
● minimum rated value	100 V
● maximum rated value	240 V
● initial value	85 V
● full-scale value	264 V
input voltage at DC	110 ... 300 V
supply voltage	
● at 50 Hz	240 V
● at 60 Hz	100 V
line frequency	50/60 Hz
line frequency	47 ... 63 Hz
wide range input	Yes
overvoltage overload capability	300 V AC for 1 s
buffering time for rated value of the output current in the event of power failure minimum	40 ms
operating condition of the mains buffering	at Vin = 187 V
input current	
● at rated input voltage 120 V	1.24 A
● at rated input voltage 230 V	0.68 A
current limitation of inrush current at 25 °C maximum	55 A
I2t value maximum	3 A²·s
fuse protection type	internal
fuse protection type in the feeder	Recommended miniature circuit breaker: from 10 A characteristic B or from 6 A characteristic C
output	
voltage curve at output	Controlled, isolated DC voltage

Subject to change without notice
© Copyright Siemens

product function output voltage controlled	Yes
product function output voltage stabilized	Yes
output voltage at DC rated value	15 V
output voltage	
● at output 1 at DC rated value	15 V
output voltage	
● at output 1 at DC	15 V
output voltage adjustable	Yes; via potentiometer
adjustable output voltage	10.5 ... 16.1 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
● on slow fluctuation of input voltage	0.1 %
● on slow fluctuation of ohm loading	0.1 %
residual ripple	
● maximum	200 mV
● typical	30 mV
voltage peak	
● maximum	300 mV
● typical	50 mV
display version for normal operation	Green LED for output voltage OK
behavior of the output voltage when switching on	No overshoot of Vout (soft start)
response delay maximum	0.5 s
voltage increase time of the output voltage	
● typical	100 ms
output current	
● rated value	4 A
● rated range	0 ... 4 A; +55 ... +70 °C: Derating 2%/K
supplied active power typical	60 W
bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
efficiency	
efficiency in percent	88.4 %
power loss [W]	
● at rated output voltage for rated value of the output current typical	7.9 W
● during no-load operation maximum	0.3 W
closed-loop control	
relative control precision of the output voltage with rapid fluctuation of the input voltage by +/- 15% typical	0.2 %
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	3 %
setting time	
● load step 10 to 90% typical	1 ms
● load step 90 to 10% typical	1 ms
protection and monitoring	
design of the overvoltage protection	< 60 V
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
● typical	5 A
overcurrent overload capability	
● when switching on	150% Iout rated typ. 200 ms
● in normal operation	overload capability 150% Iout rated typ. 200 ms
enduring short circuit current RMS value	
● maximum	5 A
measuring point for output current	Yes; 45 mV =^ 4 A
safety	
galvanic isolation between input and output	Yes
galvanic isolation	Output voltage: SELV, ES1 (IEC 62368-1), DVC As (IEC 61204-7)

Subject to change without notice
© Copyright Siemens

operating resource protection class	Class II (without protective conductor)
protection class IP	IP20
EMC	
standard	
● for emitted interference	EN 55022 Class B
● for mains harmonics limitation	not applicable
● for interference immunity	EN 61000-6-2
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus-Recognized (UL 60950, CSA C22.2 No. 60950), File E151273, NEC class 2 (acc. to UL 1310)
● EAC approval	Yes
● NEC Class 2	Yes; according to UL1310, File E151273
● SEMI F47	Yes
type of certification	
● CB-certificate	Yes
MTBF at 40 °C	2 566 680 h
standards, specifications, approvals hazardous environments	
certificate of suitability	
● IECEx	No
● ATEX	No
● ULhazloc approval	No
● FM registration	No
standards, specifications, approvals marine classification	
shipbuilding approval	Yes
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	Yes
● French marine classification society (BV)	Yes
● Det Norske Veritas (DNV)	Yes
● Lloyds Register of Shipping (LRS)	Yes
standards, specifications, approvals Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	220 kg
● during manufacturing	3.8 kg
● during operation	216 kg
● after end of life	0.14 kg
Siemens eco profile (SEP)	Siemens EcoTech
ambient conditions	
ambient temperature	
● during operation	-25 ... +70 °C; with natural convection
● during transport	-40 ... +85 °C
● during storage	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
connection method	
type of electrical connection	screw terminal
● at input	L, N: 1 screw terminal each for 0.5 ... 2.5 mm2 single-core/finely stranded
● at output	+, -: 1 screw terminal each for 0.5 ... 2.5 mm²
● for auxiliary contacts	-
mechanical data	
width × height × depth of the enclosure	54 × 90 × 53 mm
installation width × mounting height	54 mm × 130 mm
required spacing	
● top	20 mm
● bottom	20 mm
● left	0 mm
● right	0 mm

Subject to change without notice
© Copyright Siemens

fastening method	Snaps onto DIN rail EN 60715 35x7.5/15, direct mounting in different mounting positions
● DIN-rail mounting	Yes
● S7 rail mounting	No
● wall mounting	Yes
housing can be lined up	Yes
net weight	0.2 kg

further information internet links

internet link	
● to website: Industry Mall	https://mall.industry.siemens.com
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to web page: power supplies	https://siemens.com/sitop
● to website: CAx-Download-Manager	https://siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

additional information

other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Classifications

	Version	Classification
eClass	16	27-04-07-01
eClass	14	27-04-07-01
eClass	12	27-04-07-01
eClass	9.1	27-04-07-01
eClass	9	27-04-07-01
eClass	8	27-04-90-02
eClass	7.1	27-04-90-02
eClass	6	27-04-90-02
ETIM	10	EC002540
ETIM	9	EC002540
ETIM	8	EC002540
ETIM	7	EC002540
IDEA	4	4130
UNSPSC	15	39-12-10-04

Approvals Certificates

Environmental Product Declaration	
● global warming potential [CO2 eq] / during manufacturing	3.8 kg
● global warming potential [CO2 eq] / during operation	216 kg
● global warming potential [CO2 eq] / after end of life	0.14 kg
● global warming potential [CO2 eq] / total	220 kg

Environment	General Product Approval

Subject to change without notice
© Copyright Siemens

Manufacturer Declaration

Declaration of Conformity

General Product Approval

China RoHS

Maritime application

last modified: 5/5/2026

Subject to change without notice
© Copyright Siemens