SIEMENS

Data sheet 6ES7132-6FD00-2BB1



Figure similar

SIMATIC ET 200SP, digital output module, DQ 4x 24..230V AC/2A Standard Pack quantity: 10 units, suitable for BU type B1, Color code CC41, Module diagnostics

General information	
Product type designation	DQ 4x24 ... 230 V AC/2 A ST
HW functional status	From FS05
Firmware version	V1.0
● FW update possible	Yes
usable BaseUnits	BU type B1
Color code for module-specific color-coded label	CC41
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V13 / V13
● STEP 7 configurable/integrated from version	V5.5 SP3 / -
● PROFIBUS from GSD version/GSD revision	GSD Revision 5
● PROFINET from GSD version/GSD revision	GSDML V2.3
Operating mode	
● DQ	Yes
● DQ with energy-saving function	No
● PWM	No
● Oversampling	No
● MSO	No
Supply voltage	
Rated value (AC)	230 V
permissible range, lower limit (AC)	20.4 V
permissible range, upper limit (AC)	264 V
Input current	
Current consumption (rated value)	11.5 mA
Output voltage	
Rated value (AC)	230 V; 24V AC to 230V AC
Power loss	
Power loss, typ.	9 W; Active power, load voltage 230 V, all outputs loaded with 2 A, 50 Hz
Address area	
Address space per module	
● Address space per module, max.	1 byte; + 1 byte for QI information
● Inputs	1 byte; With QI

Subject to change without notice
© Copyright Siemens

● Outputs	1 byte
Hardware configuration	
Automatic encoding	
● Type of mechanical coding element	type C
Selection of BaseUnit for connection variants	
● 1-wire connection	BU type B1
● 2-wire connection	BU type B1
● 3-wire connection	BU type B1
● 4-wire connection	BU type B1 + potential distributor module
Digital outputs	
Type of digital output	Triac with zero point detection
Number of digital outputs	4
Current-sinking	No
Current-sourcing	Yes
Digital outputs, parameterizable	No
Short-circuit protection	No; When using BU type B1, a miniature, quick-response fuse with 10 A tripping current must be provided
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	5
Switching capacity of the outputs	
● with resistive load, max.	2 A
● on lamp load, max.	100 W
Output voltage	
● for signal "1", min.	20.4 V
Output current	
● for signal "1" rated value	2 A
● for signal "1" permissible range, min.	10 mA
● for signal "1" permissible range, max.	2 A
● for signal "0" residual current, max.	460 µA
Output delay with resistive load	
● "0" to "1", max.	10 ms
● "1" to "0", max.	10 ms
Parallel switching of two outputs	
● for logic links	No
● for uprating	No
● for redundant control of a load	Yes
Switching frequency	
● with resistive load, max.	10 Hz
● with inductive load, max.	0.5 Hz; Higher frequencies are possible, see Equipment Manual / Product Information
● on lamp load, max.	1 Hz
Total current of the outputs	
● Current per channel, max.	2 A
● Current per module, max.	8 A
Total current of the outputs (per module)	
horizontal installation	
— up to 40 °C, max.	8 A
— up to 50 °C, max.	6 A
— up to 60 °C, max.	4 A
vertical installation	
— up to 30 °C, max.	8 A
— up to 40 °C, max.	6 A
— up to 50 °C, max.	4 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Substitute values connectable	Yes

Subject to change without notice
© Copyright Siemens

Alarms	
● Diagnostic alarm	No
Diagnoses	
● Monitoring the supply voltage	No
● Wire break	No
● Short-circuit	No
● Group error	Yes
Diagnostics indication LED	
● Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
● Channel status display	Yes; green LED
● for channel diagnostics	No
● for module diagnostics	Yes; green/red DIAG LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	No
Isolation	
Isolation tested with	2 545 V DC/2 s (routine test)
Standards, approvals, certificates	
Suitable for safety functions	No
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	13.9 kg
— global warming potential, (during production) [CO2 eq]	5.53 kg
— global warming potential, (during operation) [CO2 eq]	8.71 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.359 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	60 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	2 000 m; On request: Installation altitudes greater than 2 000 m
Dimensions	
Width	20 mm
Height	73 mm
Depth	58 mm
Weights	
Weight, approx.	50 g
Classifications	

	Version	Classification
eClass	16	27-24-26-04
eClass	14	27-24-26-04
eClass	12	27-24-26-04
eClass	9.1	27-24-26-04
eClass	9	27-24-26-04
eClass	8	27-24-26-04
eClass	7.1	27-24-26-04
eClass	6	27-24-26-04
ETIM	10	EC001599
ETIM	9	EC001599

Subject to change without notice
© Copyright Siemens

ETIM	8	EC001599
ETIM	7	EC001599
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous





Manufacturer Declaration





General Product Approval

China RoHS





Manufacturer Declaration

Maritime application



Environment



Environment



last modified: 9/19/2025

Subject to change without notice
© Copyright Siemens