SIEMENS

Data sheet for SINUMERIK Electronic handwheel



Figure similar

Article No. : **6FC9320-5DH01**

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Input voltage	DC 24 V
Max. power consumption	20 mA
Interface	HTL
Displacement angle, signal A to B	90 °
Pulses per revolution	100
Actuating force	0.04 Nm
Output frequency	2.00 kHz
Transmission link	
to NCU/PCU, max.	25 m (82.02 ft)

Mechanical data	
Net weight	0.4 kg (0.88 lb)
Width	76.2 mm (3.00 in)
Height	76.2 mm (3.00 in)
Depth	81.8 mm (3.22 in)
Installation depth	39.4 mm (1.55 in)
Front side	IP65
Rear side	IP50

Ambient conditions	
Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Ambient temperature	
Operation	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Relative humidity	
Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CE, cULus