SIEMENS

Data sheet 3UG4622-2AA30



!!! product phase-out !!! the preferred successor is 3UG5642-2CW30 digital monitoring relay current monitoring, 22.5 mm from 0.05 to 10 A AC/DC overshoot and undershoot supply voltage: 24 V AC/DC 50 to 60 Hz DC and AC without electrical separation from the measuring circuit ON-delay and noise pulses delay 0.1 to 20 s hysteresis 0.01 to 5 A 1 changeover contact with or without fault buffer spring-loaded connection system

product brand name	SIRIUS
product designation	Current monitoring relay with digital setting
product type designation	3UG4
General technical data	
product function	Current monitoring relay
design of the display	LCD
insulation voltage for overvoltage category III according to IEC 60664	
● with degree of pollution 3 rated value	690 V
degree of pollution	3
type of voltage of the operating voltage	AC/DC
surge voltage resistance rated value	4 kV
maximum permissible voltage for protective separation	
● between auxiliary and auxiliary circuit	300 V
● between control and auxiliary circuit	300 V
shock resistance according to IEC 60068-2-27	sinusoidal half-wave 15 g / 11 ms
vibration resistance according to IEC 60068-2-6	1 ... 6 Hz: 15 mm, 6 ... 500 Hz: 2 g
mechanical service life (operating cycles) typical	10 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	100 000
thermal current of the switching element with contacts maximum	5 A
reference code according to IEC 81346-2	K
relative repeat accuracy	1 %
Substance Prohibitance (day/month/year)	05/01/2012
SVHC substance name	Lead CAS-No. 7439-92-1 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one CAS-No. 71868-10-5 Melamine CAS-No. 108-78-1 6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol CAS-No. 119-47-1
Net Weight	0.121 kg
Product Function	
product function	
● undervoltage detection	No
● overvoltage detection	No
● phase sequence recognition	No
● phase failure detection	No
● voltage monitoring	No
● current monitoring	Yes
● overcurrent detection 1 phase	Yes
● overcurrent detection 3 phase	No
● undercurrent detection 1 phase	Yes

Subject to change without notice
© Copyright Siemens

● undercurrent detection 3 phases	No
● overcurrent detection DC	Yes
● undercurrent detection DC	Yes
● current window recognition DC	Yes
● voltage window recognition 1 phase	No
● voltage window recognition 3 phase	No
● adjustable open/closed-circuit current principle	Yes
● external reset	Yes
● auto-RESET	Yes
Control circuit/ Control	
control supply voltage at AC	
● at 50 Hz rated value	24 ... 240 V
● at 60 Hz rated value	24 ... 240 V
control supply voltage at DC rated value	24 ... 240 V
Supply voltage	
type of voltage of the supply voltage	AC/DC
supply voltage 1 at AC	
● at 50 Hz rated value	24 V
● at 50 Hz	20.4 ... 26.4 V
● at 60 Hz rated value	24 V
● at 60 Hz	20.4 ... 26.4 V
supply voltage 1 at DC	20.4 ... 26.4 V
supply voltage 1 at DC rated value	24 V
Measuring circuit	
type of current for monitoring	AC/DC
measurable current	0.05 ... 15 A
measurable line frequency	40 ... 500 Hz
adjustable current response value current	
● 1	0.1 ... 10 A
● 2	0.1 ... 10 A
adjustable response delay time	
● when starting	0.1 ... 20 s
● with lower or upper limit violation	0.1 ... 20 s
adjustable switching hysteresis for measured current value	10 ... 5 000 mA
buffering time in the event of power failure minimum	10 ms
accuracy of digital display	+/-1 digit
relative temperature-related measurement deviation	5 %
internal resistance of the measuring circuit	5 mΩ
Precision	
relative metering precision	5 %
temperature drift per °C	0.1 %/°C
Communication/ Protocol	
protocol is supported IO-Link protocol	No
Auxiliary circuit	
number of NC contacts delayed switching	0
number of NO contacts delayed switching	0
number of CO contacts	
● delayed switching	1
operating frequency with 3RT2 contactor maximum	5 000 1/h
Main circuit	
number of poles for main current circuit	1
operating voltage rated value	24 V
ampacity of the output relay at AC-15	
● at 250 V at 50/60 Hz	3 A
● at 400 V at 50/60 Hz	3 A
ampacity of the output relay at DC-13	
● at 24 V	1 A
● at 125 V	0.2 A

© Copyright Siemens

● at 250 V	0.1 A
operational current at 17 V minimum	0 A
continuous current of the DIAZED fuse link of the output relay	4 A
Electromagnetic compatibility	
conducted interference	
● due to burst according to IEC 61000-4-4	2 kV
● due to conductor-earth surge according to IEC 61000-4-5	2 kV
● due to conductor-conductor surge according to IEC 61000-4-5	1 kV
field-based interference according to IEC 61000-4-3	10 V/m
electrostatic discharge according to IEC 61000-4-2	6 kV contact discharge / 8 kV air discharge
Galvanic isolation	
design of the electrical isolation	Protective separation
galvanic isolation	
● between input and output	Yes
● between the outputs	Yes
● between the voltage supply and other circuits	No
Safety related data	
product function suitable for safety function	No
Electrical Safety	
protection class IP on the front according to IEC 60529	IP20
Connections/ Terminals	
product component removable terminal for main circuit	Yes
product component removable terminal for auxiliary and control circuit	Yes
type of electrical connection	spring-loaded terminals
● for main current circuit	spring-loaded terminals
● for auxiliary and control circuit	spring-loaded terminals
type of connectable conductor cross-sections	
● solid	2x (0.25 ... 1.5 mm²)
● finely stranded with core end processing	2 x (0.25 ... 1.5 mm²)
● finely stranded without core end processing	2x (0.25 ... 1.5 mm²)
● for AWG cables solid	2x (24 ... 16)
● for AWG cables stranded	2x (24 ... 16)
connectable conductor cross-section	
● solid	0.25 ... 1.5 mm²
● finely stranded with core end processing	0.25 ... 1.5 mm²
● finely stranded without core end processing	0.25 ... 1.5 mm²
AWG number as coded connectable conductor cross section	
● solid	24 ... 16
● stranded	24 ... 16
Installation/ mounting/ dimensions	
mounting position	any
fastening method	snap-on mounting
height	94 mm
width	22.5 mm
depth	91 mm
required spacing	
● with side-by-side mounting	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
● for grounded parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm

© Copyright Siemens

— at the side	0 mm
— downwards	0 mm
● for live parts	
— forwards	0 mm
— backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm

Ambient conditions

installation altitude at height above sea level maximum	2 000 m
ambient temperature	
● during operation	-25 ... +60 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C

Approvals Certificates

Environment	General Product Approval				
Environmental Confirmations					


General Product Approval	EMV	Test Certificates	
		Type Test Certificates/Test Report	Special Test Certificate

Maritime application	other	Railway
	Confirmation	Special Test Certificate

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UG4622-2AA30
Cax online generator
https://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UG4622-2AA30
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/3UG4622-2AA30
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
https://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UG4622-2AA30&lang=en

Subject to change without notice
© Copyright Siemens



last modified: 5/26/2026

Subject to change without notice
© Copyright Siemens