SIEMENS

Data sheet 6GK5106-2BB00-2AC2



SCALANCE XC106-2, Unmanaged IE switch, 6x 10/100 Mbit/s RJ45 ports, 2x 100 Mbit/s Multimode BFOC, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply Manual available as a download .

product type designation	
product brand name	SCALANCE
product type designation	XC106-2
Technical Product Detail Page	https://i.siemens.com/1P6GK5106-2BB00-2AC2
transfer rate	
transfer rate	10, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	6; RJ45
number of 100 Mbit/s ST(BFOC) ports	
● for multimode	2
transmission method / of the optical interface	100BaseFX
interfaces / other	
number of electrical connections	
● for signaling contact	1
● for power supply	1
type of electrical connection	
● for signaling contact	2-pole terminal block
● for power supply	4-pole terminal block
operating voltage / of the signaling contacts	
● at DC / rated value	24 V
operational current / of the signaling contacts	
● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
● supply voltage / 1 / rated value	24 V
● power loss [W] / 1 / rated value	4.8 W
● supply voltage / 1 / voltage range	9.6 ... 31.2
● consumed current / 1 / maximum	0.4 A
● type of electrical connection / 1 / for power supply	4-pole terminal block
● product component / 1 / fusing at power supply input	Yes
● fuse protection type / 1 / at input for supply voltage	2,5 A / 125 V
ambient conditions	
ambient temperature	
● during operation	-40 ... +70 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
relative humidity	

Subject to change without notice
© Copyright Siemens

● at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	60 mm
height	147 mm
depth	125 mm
net weight	0.5 kg
material / of the enclosure	Polycarbonate (PC-GF10)
fastening method	
● 35 mm DIN-rail mounting	Yes
● wall mounting	Yes
● S7-300 rail mounting	Yes
● S7-1500 rail mounting	Yes
product features, product functions, product components / general	
number of automatically learnable MAC addresses	2048
product functions / management, configuration, engineering	
product function	
● multiport mirroring	No
● CoS	Yes
● switch-managed	No
PROFINET conformity class	A
product functions / redundancy	
product function	
● Parallel Redundancy Protocol (PRP)/operation in the PRP-network	Yes
● Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1	Yes
● cULus approval	Yes
● KC approval	Yes
● Regulatory Compliance Mark (RCM)	Yes
standard	
● for EMC interference emission	EN 61000-6-4 (Class A)
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
standards, specifications, approvals / hazardous environments	
certificate of suitability	
● ATEX	Yes
● UKEX	Yes
● IECEx	Yes
● ULhazloc approval	Yes
● CCC / for hazardous zone according to GB standard	Yes
● FM registration	Yes
standards, specifications, approvals / other	
certificate of suitability	
● RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
standards, specifications, approvals / marine classification	
certificate of suitability / shipbuilding approval / note	Certifications marked 'No' are currently under renewal.
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Chinese Classification Society (CCS)	No
● Det Norske Veritas (DNV)	No

Subject to change without notice
© Copyright Siemens

● Korean Register of Shipping (KRS)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
● Polski Rejestr Statkow (PRS)	No
● Royal Institution of Naval Architects (RINA)	Yes
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	220.3 kg
● during manufacturing	32.08 kg
● during operation	187.75 kg
● after end of life	0.48 kg
product functions / general	
laser protection class	LED Class 1
warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)
Approvals / Certificates	
Environmental Product Declaration	
● global warming potential [CO2 eq] / during manufacturing	32.08 kg
● global warming potential [CO2 eq] / during operation	187.75 kg
● global warming potential [CO2 eq] / after end of life	0.48 kg
● global warming potential [CO2 eq] / total	220.3 kg

Environment	General Product Approval		
	China RoHS	Declaration of Conformity	Manufacturer Declaration

General Product Approval	
Miscellaneous	China RoHS

Subject to change without notice
© Copyright Siemens

EMV	For use in hazardous locations		Maritime application
	FM	CCC-Ex	

Maritime application
NK / Nippon Kaiji Ky-okai

Industrial Communication
PROFINET

last modified: 8/28/2026

Subject to change without notice
© Copyright Siemens