SIEMENS

Data sheet 6DL1193-6TP00-0DP0

Siemens EcoTech

SIMATIC ET 200SP HA, terminal block, type P0, 64 push-in terminals, new load group, width: 45 mm



Figure similar

General information	
Product type designation	Type P0
Product function	
● I&M data	Yes
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC / 10 A (MCB with tripping characteristic type B or C, quick-response device protection fuse with sufficient breaking capacity, electronic fuse with characteristic according to type B or C)
Input current	
Current consumption, max.	640 mA; With one 20 mA encoder supply per channel
Encoder supply	
Number of outputs	32
Output voltage (DC)	24 V
24 V encoder supply	
● Short-circuit protection	Yes; Per output, thermal
● Output current, max.	20 mA; per output
● Output current per module, max.	640 mA
Current carrying capacity	
up to 70 °C, max.	10 A; Permitted load current of the potential group depending on the number of terminal blocks
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
● support of potential groups	Yes
● New potential group	Yes
● Potential group continued from the left	No
Slots	
● Number of slots	1
Potential separation	
between backplane bus and supply voltage	Yes; 3 000 V DC/1 min, type test
between potential groups (power bus)	Yes; 1 500 V DC/1 min, type test (SELV / PELV to functional ground FE)
between process terminals and supply voltage	Yes; 1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	

Subject to change without notice
© Copyright Siemens

● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C

Dimensions

Width	45 mm
Height	175 mm
Depth	77 mm

Weights

Weight, approx.	155 g

Classifications

	Version	Classification
eClass	16	27-24-26-07
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603
ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval

CE EG-Konf. | Miscellaneous | UKCA | UL | KC | RCM

General Product Approval

EAC | China RoHS | Miscellaneous | CE EG-Konf. | Manufacturer Declaration | UKCA

For use in hazardous locations

IECEx | Declaration of Conformity | CCC | UL | ATEX | IECEx

For use in hazardous locations	Maritime application				
Miscellaneous	ABS	BUREAU VERITAS	DNV	LRS	NK / Nippon Kaiji Kyokai

Maritime application	Environment

Subject to change without notice
© Copyright Siemens

CCS (China Classification Society)

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens