SIEMENS

Data sheet 6ES7331-7NF00-0AB0



Figure similar

spare part SIMATIC S7-300, analog input SM 331, isolated, 8 AI; +/-5/10V, 1-5 V, +/-20 mA, 0/4 to 20 mA, 16 bit (55 ms), single-point grounding (50 V COM.), 1x 40-pole

General information	
Product function	
● Isochronous mode	No
Input current	
from backplane bus 5 V DC, max.	130 mA
Power loss	
Power loss, typ.	0.6 W
Analog inputs	
Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	50 V; Permanent
permissible input current for current input (destruction limit), max.	32 mA
Input ranges	
● Voltage	Yes
● Current	Yes
● Thermocouple	No
● Resistance thermometer	No
● Resistance	No
Input ranges (rated values), voltages	
● 0 to +10 V	No
● 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	2 MΩ
● 1 V to 10 V	No
● -1 V to +1 V	No
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	2 MΩ
● -2.5 V to +2.5 V	No
● -250 mV to +250 mV	No
● -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	2 MΩ
● -50 mV to +50 mV	No
● -500 mV to +500 mV	No
● -80 mV to +80 mV	No
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	250 Ω
● -10 mA to +10 mA	No

Subject to change without notice
© Copyright Siemens

● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	250 Ω
● -3.2 mA to +3.2 mA	No
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	250 Ω
Input ranges (rated values), thermocouples	
● type B	No
● type C	No
● Type E	No
● Type J	No
● Type K	No
● Type L	No
● Type N	No
● Type R	No
● Type S	No
● Type T	No
● Type U	No
● Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
● Cu 10	No
● Ni 100	No
● Ni 1000	No
● LG-Ni 1000	No
● Ni 120	No
● Ni 200	No
● Ni 500	No
● Pt 100	No
● Pt 1000	No
● Pt 200	No
● Pt 500	No
Input ranges (rated values), resistors	
● 0 to 150 ohms	No
● 0 to 300 ohms	No
● 0 to 600 ohms	No
● 0 to 6000 ohms	No
Cable length	
● shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit; Unipolar: 15/15/15/15 bit; bipolar: 15 bit + sign/15 bit + sign/15 bit + sign/15 bit + sign
● Integration time, parameterizable	Yes; 10/ 16.67/ 20/ 100 ms
● Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10 Hz
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
● for current measurement as 2-wire transducer	Yes; with external transmitter; possible with separate supply for transmitter
● for current measurement as 4-wire transducer	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.1 %; At Ucm = 0 V or ±0.7 % at Ucm = 50 V
● Current, relative to input range, (+/-)	0.3 %; At Ucm = 0 V or ±0.9 % at Ucm = 50 V
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.05 %
● Current, relative to input range, (+/-)	0.05 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	

© Copyright Siemens

● Diagnostic alarm	Yes; Parameterizable
● Limit value alarm	Yes; Parameterizable, channels 0 and 2
Diagnoses	
● Diagnostic information readable	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
● between the channels	No
● between the channels, in groups of	2
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Connection method	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	272 g

Classifications

	Version	Classification
eClass	16	27-24-22-01
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous

Metrological Approval

General Product Approval

China RoHS

Manufacturer Declaration

EMV

For use in hazardous locations

Subject to change without notice
© Copyright Siemens



FM





Miscellaneous

CCC-Ex

Maritime application







NK / Nippon Kaiji Kyokai





Maritime application

CCS (China Classification Society)

last modified: 4/7/2025

Subject to change without notice
© Copyright Siemens